

SAFETY DATA SHEET

1. Identification

Product identifier Proprietary Solvent Formula III-2, 200 Proof

Other means of identification

Synonyms Denatured Alcohol

Recommended use General purpose solvent.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc.

Address 1101 Isaac Shelby Drive
Shelbyville, KY 40065
USA

Telephone 502.232.7600

Fax 502.633.6100

Company Name Greenfield Global USA Inc.

Address 58 Vale Road
Brookfield, CT 06804
USA

Telephone 203.740.3471

Fax 203.740.3481

Emergency phone number

USA CHEMTREC: 1.800.424.9300 (CCN 17213)

International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Serious eye damage/eye irritation Category 2

Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 1 (central nervous system, optic nerve)

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. Causes serious eye irritation. Suspected of causing cancer. Causes damage to organs (central nervous system, optic nerve).

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Water	7732-18-5	< 5
Ethyl alcohol	64-17-5	87 - < 92
Methanol	67-56-1	3.66
Ethyl acetate	141-78-6	1.92
2-Pentanone, 4-methyl-	108-10-1	1.88
Heptane	142-82-5	0.96

Composition comments All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Narcosis. Headache. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 ml.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	PEL	410 mg/m ³
		100 ppm
Ethyl acetate (CAS 141-78-6)	PEL	1400 mg/m ³
		400 ppm
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm
Heptane (CAS 142-82-5)	PEL	2000 mg/m ³
		500 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³
		200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	STEL	300 mg/m3
		75 ppm
	TWA	205 mg/m3
Ethyl acetate (CAS 141-78-6)		50 ppm
	TWA	1400 mg/m3
Ethyl alcohol (CAS 64-17-5)		400 ppm
	TWA	1900 mg/m3
Heptane (CAS 142-82-5)		1000 ppm
	Ceiling	1800 mg/m3
		440 ppm
Methanol (CAS 67-56-1)		350 mg/m3
	TWA	85 ppm
	STEL	325 mg/m3
		250 ppm
	TWA	260 mg/m3
		200 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Pentanone, 4-methyl- (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)

Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Chemical goggles are recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-173.2 °F (-114 °C)
Initial boiling point and boiling range	176 °F (80 °C)
Flash point	57.2 - 62.6 °F (14.0 - 17.0 °C) Closed cup
Evaporation rate	Expected to be rapid.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	3.3 % v/v
Flammability limit - upper (%)	19 % v/v
Vapor pressure	44.6 mm Hg (5.94 kPa)
Vapor density	1.6 (air =1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Completely soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	685.4 °F (363 °C) (Ethyl alcohol)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May be absorbed through the skin. Prolonged skin contact may cause temporary irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Narcosis. Headache. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 ml.

Information on toxicological effects

Acute toxicity May be harmful if swallowed.

Components	Species	Test Results
2-Pentanone, 4-methyl- (CAS 108-10-1)		
Acute		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Oral		
LD50	Rat	3200 mg/kg
Ethyl acetate (CAS 141-78-6)		
Acute		
Dermal		
LD50	Rabbit	> 18000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	58.6 mg/l, 4 hours
Oral		
LD50	Rat	10170 mg/kg
Ethyl alcohol (CAS 64-17-5)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	117 - 125 mg/l, 4 Hours
Oral		
LD50	Rat	10470 mg/kg

Components	Species	Test Results
Heptane (CAS 142-82-5)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 29.3 mg/l, 4 Hours
Oral		
LD50	Rat	15000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
2-Pentanone, 4-methyl- (CAS 108-10-1)	2B Possibly carcinogenic to humans.	
NTP Report on Carcinogens		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not regulated.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Causes damage to organs (central nervous system, optic nerve).	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
2-Pentanone, 4-methyl- (CAS 108-10-1)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 3682 mg/l, 24 hours
Fish	LC50	Pimephales promelas 505 mg/l, 96 Hours
<i>Chronic</i>		
Crustacea	EC50	Daphnia magna 78 mg/l, 21 days
Fish	NOEC	Pimephales promelas 57 mg/l, 31 days
Ethyl alcohol (CAS 64-17-5)		
Aquatic		
Algae	EC10	Freshwater algae 11.5 mg/l, 72 hours
	EC50	Freshwater algae 275 mg/l, 72 hours
		Marine water algae 1900 mg/l
	NOEC	Marine water algae 1580 mg/l
Fish	LC50	Freshwater fish 11200 mg/l, 24 hours
	NOEC	Freshwater fish 250 mg/l
Invertebrate	EC50	Freshwater invertebrate 5012 mg/l, 48 hours

Components		Species	Test Results
		Marine water invertebrate	857 mg/l, 48 hours
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestrial			
Plant	EC50	Terrestrial plant	633 mg/kg dw
Methanol (CAS 67-56-1)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	> 10000 mg/l, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	15400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Pentanone, 4-methyl- (CAS 108-10-1)	1.31
Heptane (CAS 142-82-5)	4.66
Methanol (CAS 67-56-1)	-0.77

Mobility in soil The product is soluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1987
UN proper shipping name	Alcohols, n.o.s.
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	172, IB2, T7, TP1, TP8, TP28
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number UN1987
UN proper shipping name Alcohols, n.o.s.
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1987
UN proper shipping name ALCOHOLS, N.O.S.
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant No.
EmS F-E, S-D
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Pentanone, 4-methyl- (CAS 108-10-1)	Listed.
Ethyl acetate (CAS 141-78-6)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methanol (CAS 67-56-1)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
 Serious eye damage or eye irritation
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-Pentanone, 4-methyl-	108-10-1	1.88
Methanol	67-56-1	3.66

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

2-Pentanone, 4-methyl- (CAS 108-10-1)

Methanol (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-Pentanone, 4-methyl- (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl acetate (CAS 141-78-6) Low priority

Ethyl alcohol (CAS 64-17-5) Low priority

US state regulations

US. Massachusetts RTK - Substance List

2-Pentanone, 4-methyl- (CAS 108-10-1)

Ethyl acetate (CAS 141-78-6)

Ethyl alcohol (CAS 64-17-5)

Heptane (CAS 142-82-5)

Methanol (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

2-Pentanone, 4-methyl- (CAS 108-10-1)

Ethyl acetate (CAS 141-78-6)

Ethyl alcohol (CAS 64-17-5)

Heptane (CAS 142-82-5)

Methanol (CAS 67-56-1)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Pentanone, 4-methyl- (CAS 108-10-1)

Ethyl acetate (CAS 141-78-6)

Ethyl alcohol (CAS 64-17-5)

Heptane (CAS 142-82-5)

Methanol (CAS 67-56-1)

US. Rhode Island RTK

2-Pentanone, 4-methyl- (CAS 108-10-1)

Ethyl acetate (CAS 141-78-6)

Ethyl alcohol (CAS 64-17-5)

Heptane (CAS 142-82-5)

Methanol (CAS 67-56-1)

California Proposition 65



WARNING: This product can expose you to chemicals including 2-Pentanone, 4-methyl-, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: November 4, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: March 28, 2014

Methanol (CAS 67-56-1) Listed: March 16, 2012

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Pentanone, 4-methyl- (CAS 108-10-1)

Ethyl acetate (CAS 141-78-6)

Heptane (CAS 142-82-5)

Methanol (CAS 67-56-1)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-October-2018
Revision date	07-February-2019
Version #	02
HMIS® ratings	Health: 4* Flammability: 3 Physical hazard: 0

Disclaimer This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found at <http://www.greenfield.com/tc-po-us/>. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.