

+1.703.527.3887 (INT)

SAFETY DATA SHEET

SDA 18, 190 Proof

This SDS is valid for all grades and catalog #s

1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

Product Identifier: Denatured Ethanol

Synonyms: Denatured Ethanol 18; SDA 18, 190; Denatured Ethanol; Ethanol

denatured with Vinegar

Other means of identification: CAS No. 64-17-5

EINECS No. 200-578-6

Recommended use of the chemical and restrictions on use:

General purpose organic solvent. Vinegar manufacturing.

Supplier Details:

Greenfield Global USA, Inc. Greenfield Global USA, Inc.

58 Vale Road, Brookfield, 1101 Isaac Shelby Drive, Shelbyville,

CT 06804, USA.

Tel: 203.740.3471

Fax: 203.740.3481

KY 40065, USA.

Tel: 502.232.7600

Fax: 502.633.6100

CCN17213 CCN17213

Emergency Contact: CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

2. HAZARDS IDENTIFICATION

Emergency Overview:

This material is HAZARDOUS by OSHA Hazard Communication definition. Flammable Liquid. Material can burn with little or no visible flame. May be irritating to the eyes, skin, and respiratory system. May cause central nervous system depression.

OSHA Hazards:


Flammable liquid, Target Organ Effect, Irritant

Target Organs:

Central nervous system, Heart, Liver



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)
NFPA +1.703.527.3887 (INT)



GHS label elements, including precautionary statements





Signal Word: WARNING!

Hazard statement(s)

H226 Flammable liquid and vapor H319 Causes serious eye irritation.

Precautionary statement(s)

P501 Dispose of contents and container to an approved waste disposal plant.

P240 Ground/bond container and receiving equipment.
P337 + P313 If eye irritation persists: Get medical attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Seek

medical attention.

P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

P210 Keep away from heat, sparks, open flames, and hot surfaces. No

smoking.

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P243 Take precautionary measures against static discharge.

P241 Use explosion-proof electrical, ventilating, and lighting equipment.



P242 Use only non-sparking tools. +1.703.527.3887 (INT)

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye and face protection.

GHS Classification(s)

Eye irritation (Category 2)

Flammable Liquids (Category 3)

Skin irritation (Category 2)

Specific target organ toxicity - single exposure (Category 3)

Other hazards which do not result in classification:

Potential Health Effects:

ETHANOL

Organ	Description
Eyes	Causes eye irritation. May cause painful sensitization to light. May cause chemical conjunctivitis and corneal damage.
Ingestion	May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause systemic toxicity with acidosis. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.
Inhalation	High concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause narcotic effects in high concentration. Vapors may cause dizziness or suffocation.
Skin	Causes moderate skin irritation. May cause dermatitis by de-fatting the skin from prolonged or repeated contact.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical identity: Alcohol

Common name / Synonym: Denatured Ethanol 18; SDA 18, 190; Denatured Ethanol; Ethanol

Denatured with Vinegar

 CAS number:
 64-17-5

 EINECS number:
 200-578-6

 ICSC number:
 0044

RTECS #: KQ6300000 UN #: UN1170 EC #: 603-002-00-5

% Volume	Material	CAS
3.6	Acetic Acid	64-19-7
38.0	Ethyl Alcohol	64-17-5
58.4	Water	7732-18-5



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)
4. FIRST AID MEASURES +1.703.527.3887 (INT)

General advice

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Skin

Immediately flush affected area with plenty of water while removing contaminated clothing. Wash contaminated clothing before reuse. Contact a doctor. If irritation persists, get medical attention.

Inhalation

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

Eves

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

Ingestion

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

Note to Physician

Symptoms vary with alcohol level of the blood. Mild alcohol intoxication occurs at blood levels between 0.05- 0.15 %. Approximately 25% of individuals show signs of intoxication at these levels. Above 0.15% the person is definitely under the influence of ethanol; 50-95% of individuals are clinically intoxicated at these levels. Severe poisoning occurs when the blood is ethanol level is 0.3- 0.5%. Above 0.5% the individual will be comatose and death can occur. The unabsorbed ethanol should be removed by gastric lavage after intubating the patient to prevent aspiration. Avoid the use of depressant drugs or the excessive administration of fluids.

5. FIRE FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

SMALL FIRE: Use dry chemicals, CO2, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam. Cool all affected containers with flooding quantities of water.

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Carbon monoxide is expected to be the primary hazardous combustion product.

Special protective equipment and precautions for firefighters:

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water.

Unusual Fire and Explosion Hazards:

May produce a floating fire hazard.

SDS: 1022 Revision Date: 09.06.16 Revision Number: 4.0 Initials: EF

Page 4 of 13



• Static ignition hazard can result from handling and use.

+1.703.527.3887 (INT)

- · Vapors may settle in low or confined spaces.
- Vapors may travel to source of ignition and flash back.

Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may only be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire.

Flammable Properties

Classification

OSHA/NFPA Class IC Flammable Liquid.

Flash point

41°C (106°F) - closed cup

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.

Methods and materials for containment and cleaning up:

Highly flammable liquid. Eliminate all sources of ignition. All equipment used when handling this product must be grounded. A vapor suppressing foam may be used to reduce vapors. Do not touch or walk through spilled material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling:

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Open and handle container with care. Metal containers involved in the transfer of this material should be grounded and bonded.

Conditions for safe storage, including any incompatibilites:

Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Consult local fire codes for additional storage information.



+1.703.527.3887 (INT)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters, e.g., occupational exposure limit values or biological limit values:

Occupational Exposure Limits

Component	Source	Type	Value	Note
Ethyl alcohol	US (ACGIH)	STEL	1000 ppm	Upper Respiratory Tract irritation Confirmed animal carcinogen with unknown relevance to humans
Ethyl alcohol	US (OSHA)	TWA	1000 ppm / 1,900 mg/m3	29 CFR 1910.1000 Table Z-1 Limits for Air Contaminants.
Ethyl alcohol	US (OSHA)	IDHL	3300 ppm	None
Acetic Acid	US (OSHA)	TWA	10 ppm	
Acetic Acid	US (OSHA)	STEL	15 ppm	

Appropriate engineering controls:

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

Individual protection measures, such as personal protective equipment:

Respiratory protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

Skin and body protection:

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES



Appearance (physical state, color, etc.)	Liquid. Colorless liquid / invisible vapor. +1.703.527.3887 (INT)
Odor	Characteristic, vinegar
Freezing point	-7°C (19°F)
Initial boiling point and boiling range	89°C (192°F)
Flash point	41°C (106°F) - closed cup
Evaporation rate	Specific data not available - expected to be rapid.
Flammability (solid, gas)	Combustible
Upper / Lower flammability or explosive limits	3.3%(V) / 19%(V) (for 100% ethanol)
Vapor pressure	59.5 hPa (44.6 mmHg) at 20 °C (68 °F) (for 100% ethanol)
Vapor Density	1.6
Relative Density	7.802 lb/gal
Solubility(ies)	completely soluble
Decomposition temperature	Not pertinent
Formula (ACETIC ACID)	C2H4O2
Formula (ETHANOL)	C2H6O
Formula (WATER)	H2O
Molecular Weight (ACETIC ACID)	60.05 g/mol
Molecular Weight (ETHANOL)	46.07 g/mol
Molecular Weight (WATER)	18.02 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Vapors may form explosive mixture with air.
Conditions to avoid (e.g., static discharge,	Heat, flames, and sparks. Extreme temperatures and direct
shock or vibration)	sunlight.
Incompatible materials	Alkali metals, Ammonia, Oxidizing agents, Peroxides, Strong Inorganic Acids
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions Carbon oxides

11. TOXICOLOGICAL INFORMATION

• Ethyl Alcohol 64-17-5

Signs and Symptoms of Exposure

Central nervous system depression, narcosis, damage to the heart. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Product Summary:

Ethanol is not toxic by OSHA standards. Coingestion of sedative hypnotics or tranquilizers can increase the toxic affects of ethanol.



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA) Acute Toxicity: +1.703.527.3887 (INT)

			- 117 00:027 :0007 (1141)
LC50 (inhl)	Rat	20000ppm	10 hrs.
LC50 (Oral)	Rat	7060mg/Kg BWT	
LDLo (Oral)	Human	1400 mg/Kg BWT	

Irritation:

Eyes (ETHANOL)

Eye exposure to Ethanol generally causes transient pain, irritation, and reflex lid closure. A foreign-body sensation may persist for one to two days. Vapors produce transient stinging and tearing, but no apparent adverse effects. Transiently impaired preception of color may occur with acute ingestion or chronic alcoholism. Standard Draize eye test (rabbit) - Dose: 500 mg Reaction: Severe Dose: 500 mg/24 hrs Reaction: Mild

Skin

Standard Draize skin test (rabbit) - Dose: 20 mg/24 hrs Reaction: Moderate Repeated exposure may cause skin dryness or cracking.

Carcinogenicity

IARC: Not classifiable as a human carcinogen. ACGIH: Not classifiable as a human carcinogen. NTP: Not classifiable as a human carcinogen. OSHA: Not classifiable as a human carcinogen.

Other Hazards

Organ	Description
Eyes	Irritating to the eyes. May cause painful sensitization to light. May cause chemical conjunctivitis and
	corneal damage.
Ingestion	May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause systemic toxicity
Ingestion	with acidosis. Advanced stages can lead to respiratory failure, kidney failure, coma, and death.
	Inhalation of high concentrations may cause central nervous system effects characterized by nausea,
Inhalation	headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause narcotic
	effects in high concentration. Vapors may cause dizziness or suffocation.
Skin	Mildly irritating to the skin. May cause dermatitis by de-fatting the skin from prolonged or repeated
Skill	contact.
Chronic	Prolonged exposure can cause liver, kidney, and heart damage. Long term exposure can cause loss of
Cilionic	appetite, weight loss, nervousness, memory loss, mental retardation.

• Water 7732-18-5

Product Summary:

Do data available for the teratogenic, mutagenic, or reproductive toxicity effects of this product.

Carcinogenicity

SDS: 1022 Revision Date: 09.06.16 Revision Number: 4.0 Initials: EF

Page 8 of 13



IARC: No component of this product present at levels greater than or equal to 0.1% is identified as 127 by 1870 (INT) confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other Hazards

Organ	Description
Inhalation	May cause respiratory tract irritation upon inhalation.

Acetic Acid 64-19-7

Product Summary:

No data available for the teratogenicity or reproductive effects. Acetic acid is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Ingestion or inhalation of concentrated Acetic Acid causes damage to tissues of the respiratory and digestive tracts.

Acute Toxicity:

•			
LC50 (Inhalation)	Rat	11.4 mg/L	4 hours
LD50 (Dermal)	Rabbit	1,112 mg/kg	
LD50 (Oral)	Rat	3,310 mg/kg	

Irritation:

Eyes

Rabbit- Corrosive to eyes - 24 hours

Signs and Symptoms of Exposure (ACETIC ACID)

Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.



NTP: No component of this product present at levels greater than or equal to 0.1% is iden##feptos.52703887 (INT) anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other Hazards

Organ	Description
Eyes	Causes eye burns, Can cause severe eye burns.
Ingestion	Harmful if ingested.
Inhalation	May be harmful if inhaled. Material is extremely damaging to the upper respiratory tract.
Skin	Causes skin burns.

12. ECOLOGICAL INFORMATION

• Ethyl Alcohol 64-17-5

Ecotoxicity (aquatic and terrestrial, where available):

Acute Fish toxicity (ETHANOL)

LC50 / 96 HOUR Oncorhynchus mykiss (rainbow trout) > 10,000 mg/l LC50 / 96 HOUR Pimephales promelas (fathead minnow) > 13,400 mg/l

Toxicity to aquatic plants (ETHANOL)

Growth inhibition / 96 HOURS Chlorella vulgaris (Fresh water algae) 1,000 mg/l

Toxicity to microorganisms (ETHANOL)

Toxicity Threshold / Pseudomonas putida 6,500 mg/l Summary: Inhibition of cell multiplication begins.

Persistence and degradability:

Biodegradation is expected.

Bioaccumulative potential:

Biaccumulation is unlikely

• Water 7732-18-5

Ecotoxicity (aquatic and terrestrial, where available): Ecotoxicity



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)
Not Applicable +1.703.527.3887 (INT)

Persistence and degradability:

No data available

Bioaccumulative potential:

No data available

Other adverse effects:

No data available

Acetic Acid 64-19-7

Ecotoxicity (aquatic and terrestrial, where available):

Acute Toxicity to Fish (ACETIC ACID)

LC50 / 96 hours Rainbow Trout - > 1,000 mg/L LC50 / 96 hours Fathead Minnow - 79- 88 mg/L

Persistence and degradability:

Biodegradation is expected.

Bioaccumulative potential:

No data available

Other adverse effects:

No data available

13. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. TRANSPORT INFORMATION

Description of waste residues and information on their safe handling and methods of disposal:

UN number UN1170



UN proper shipping name	Ethanol - βφ! φήρ3:527.3887 (INT)
Transport hazard class(es)	3
Packing group (if applicable)	III

IMDG

UN-Number: UN1170 Class: 3 Packing Group: III

EMS-No: F-E, S-D

Proper shipping name: Ethanol Solution

Marine pollutant: No

IATA

UN-Number: UN1170 Class: 3 Packing Group: III

Proper shipping name: Ethanol Solution

15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

All ingredients are on the following inventories or are exempted from listing

Country	Notification	
Australia	AICS	
Canada	DSL	
China	IECS	
European Union	EINECS	
Japan	ENCS/ISHL	
Korea	ECL	
New Zealand	NZIoC	
Philippines	PICCS	
United States of America	TSCA	

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard Chronic Health Hazard Fire Hazard



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA) CERCLA +1.703.527.3887 (INT)

Acetic Acid CAS-No. 64-19-7, RQ: 5,000 lbs

Massachusetts Right To Know Components

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Acetic acid CAS-No. 64-19-7 Revision Date 1993-04-24

Pennsylvania Right To Know Components

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Acetic acid CAS-No. 64-19-7 Revision Date 1993-04-24

New Jersey Right To Know Components

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Acetic acid CAS-No. 64-19-7 Revision Date 1993-04-24

16. OTHER INFORMATION: INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

Disclaimer

Greenfield Global USA, Inc. believes that the information on this SDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, Greenfield Global USA, Inc. does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable. Information is correct to the best of our knowledge at the date of the SDS publication.