

 PRODUCT NAME:
 SDAG-2 (95%)

 MSDS NO:
 2161

PAGE 1 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 1- IDENTIFICATION OF SUBSTANCE AND OF SUPPLIER

PRODUCT NAME: SDAG-2 (95%)

SYNONYMS: Denatured Ethanol, Ethyl Alcohol denatured with Methanol

CHEMICAL FAMILY: Alcohols

RECOMMENDED USE: As a solvent in the manufacture of: adhesives and binders, cellulose coatings, cellulose intermediates and industrial collodions, cleaning solutions, cosmetics for external use, disinfectants, embalming fluids, explosives, fungicides, industrial detergents and soaps, inks, insecticides, insulin, natural and synthetic resin, coatings, petroleum products, photoengraving and rotogravure dyes, photoengraving and rotogravure solutions, photographic films and emulsions, plastics, polishes, sodium hydrosulphite, soldering flux, solvents and thinners, stains for wood and other materials, sterilizing and preserving solutions, transparent sheeting, .other miscellaneous.

RESTRICTIONS ON USE: Refer to the alcohol control authority in country in which the product is to be used– Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in US etc.

SUPPLIER: Commercial Alcohols, a Trade name of GreenField Global Inc. 6985 Financial Drive, Mississauga, Ontario, Canada L5N 0G3 Web page: http://www.greenfield.com/

> NON-EMERGENCY INFORMATION PHONE NUMBER: (905) 790-7500 EMERGENCY PHONE NUMBER: CANUTEC (613) 996-6666

SECTION 2– HAZARDS IDENTIFICATION

GHS label elements, including precautionary statements:



Signal Word: DANGER!

Hazard statement(s)

- H225 Highly flammable liquid and vapor.
- H302 Harmful if swallowed.
- H315 + H320 Causes skin and eye irritation
- H335 May cause respiratory irritation.
- H370 May cause damage to organs.

Precautionary statement(s)

- P501 Dispose of contents and container to an approved waste disposal plant.
- P240 Ground/bond container and receiving equipment.
- P337 + P313 If eye irritation persists: Get medical attention.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO INFORMATION AND RECOMMEN-DATIONS CONTAINED HEREIN.



PRODUCT NAME:SDAG-2 (95%)MSDS NO:2161

PAGE 2 OF 9 EFFECTIVE DATE: February 14, 2018

(SECTION 2 HAZARDS IDENTIFICATION CONTINUED)

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with
water.	
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P210	Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P243	Take precautionary measures against static discharge.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye and face protection.

GHS Classification(s)

Flammable Liquids (Category 2) Acute toxicity, Oral (Category 4) Eye irritation (Category 2B) Skin irritation (Category 2) Specific target organ toxicity - single exposure (Category 1) Specific target organ toxicity - single exposure (Category 3)

Other hazards which do not result in classification:

Potential health Effects:

Organ	Description
Eyes	Can cause eye irritation. Common symptoms include stinging, tearing, and redness.
Ingestion	Toxic if swallowed. Short term overexposure can cause drunkenness, depression of the cen- tral nervous system, nausea, vomiting, diarrhea, liver damage, and death.
Inhalation	Toxic if inhaled. Upper respiratory tract irritation, drowsiness and dizziness may occur.
Skin	Toxic if absorbed through the skin. May cause dermatitis by defatting the skin from pro- longed or repeated contact.
Chronic	 Effects of Repeated Overexposure: Long term repeated oral exposure to ethanol may result in the development of progressive liver injury with fibrosis. Overexposure to methanol may cause eye damage and liver or kidney damage. Other Health Hazards: Repeated ingestion of ethanol by pregnant mothers has been shown to adversely affect the development of the fetal central nervous system and progression of fetal alcohol syndrome. Medical Conditions Aggravated by Overexposure: Repeated exposure to ethanol may aggravate previous liver condition. Skin contact may aggravate dermatitis.



PRODUCT NAME: MSDS NO: SDAG-2 (95%)

PAGE 3 OF 9

EFFECTIVE DATE: February 14, 2018

SECTION 3– COMPOSITION AND INFORMATION ON INGREDIENTS

CHEMICAL NAME:SPECIALLY DENATURED ETHYL ALCOHOL SDAG-2 (95%)COMMON NAME/ SYNONYMDENATURED ALCOHOL, DENATURED ETHANOL, ETHANOL DENATURED WITH METHANOL

INGREDIENT	% VOLUME	CAS NO.	EINECS NO.
Ethyl Alcohol	86.4	64-17-5	200-578-6
(Methanol	9.1	67-56-1	200-659-6
Water	balance	7732-18-5	231-791-2

SECTION 4– FIRST AID MEASURES

<u>INHALATION</u>	 Remove victim to fresh air. Artificial respiration should be given if breathing has stopped and cardiopulmonary resuscitation if heart has stopped. Oxygen may be given if necessary. Seek medical attention immediately.
<u>Skin</u>	 Flush contaminated area with water for at least 20 minutes. Remove contaminated clothing under running water. Completely decontaminate clothing before re-use, or discard. If irritation occurs seek medical attention.
<u>Eyes</u>	 Immediately flush eyes with water for at least 20 minutes, holding the eyelids open. Seek medical attention immediately.
INGESTION	 Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim drink about 250ml (8fl. oz.) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Seek medical assistance.
<u>NOTES TO</u> PHYSICIAN	 This product contains 4.8% v/v of methanol, a toxic substance having produced blindness and other serious effects on vision, as well as death. However, this product also contains the accepted antidote, ethanol (86.4% v/v).

SECTION 5- FIRE FIGHTING MEASURES

<u>Extinguishing</u> <u>Media</u>	 Apply alcohol-type or all-purpose-type foams by manufacturers' recommended techniques for large fires. Use carbon dioxide or dry chemical media for small fires. Water is generally unsuitable for large open pools of alcohol and may help to spread the fire.
Unusual Fire and Explosion Hazards	• Vapours form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from handling point.
<u>Special</u> FireFighting Procedures	 Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapours; reignition is possible. Use self-contained breathing apparatus and protective clothing.



2161



PRODUCT NAME: MSDS NO: SDAG-2 (95%) 2161

PAGE 4 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 6- ACCIDENTAL RELEASE MEASURES

<u>Spill</u>	 Contain spilled material. Provide adequate ventilation. Provide adequate personnel protective equipment for responders. Remove sources of heat, sparks or flames. Spill should be collected in suitable containers or absorbed on a suitable absorbent material for subsequent disposal. Such containers used to contain spilled material and absorbent should be sealed off, otherwise the collected alcohol will evaporate from them.
<u>Waste</u> Disposal	• Waste material should be disposed of in an approved incinerator or in a designated landfill site, in compliance with all federal, provincial and local government regulations.

SECTION 7- HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing	 Keep away from heat, sparks and flames. Keep container closed when not in use. Use with adequate ventilation. Avoid breathing vapours. Avoid contact with eyes and skin. Wash exposed skin thoroughly after handling. Take precautions to prevent static electricity build-up when transferring contents.
OTHER PRECAUTIONS	 Good personal hygiene practices are suggested, such as abstaining from eating, drinking and smoking in the workplace.

SECTION 8- EXPOSURE CONTROLS/ PERSONNEL PROTECTION

RESPIRATORY EQUIPMENT	 Up to 1000 ppm, an approved organic vapour cartridge respirator can be used. For concentrations above 1000 ppm, an air-supplying respirator is recommended. The user should consult a respirator guide, such as the Canadian Standards Association's guide Z94.4-M1982.
VENTILATION	 The ventilation system should be non-sparking, grounded and separate from other exhaust ventilation systems. Local ventilation is recommended when handling.
PROTECTIVE GLOVES	Neoprene, butyl or natural rubber.
EYE PROTECTION	Chemical resistant monogoggles when handling
OTHER PROTECTIVE EQUIPMENT	• Eye bath, safety shower and other protective equipment as required.



Product Name: MSDS NO:

SDAG-2 (95%) 2161

PAGE 5 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 9– PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Colourless liquid				
ODOUR	Typical lower alcohol odour				
ODOUR THRESHOLD	Approximately 0.1 to 5100 ppm for ethyl alcohol and 4.3 to 5900 ppm for methanol, as reported in appendix 1 of the Canadian Standards Association guide Z94.4-M1982.				
РН	Not Applicable				
MELTING./ FREEZING POINT	Approximately minus 115 deg. C				
BOILING POINT RANGE	76.8 - 78.1deg. C				
FLASH POINT	16 (Tag closed cup, ASTM D-56)				
EVAPORATION RATE	1.7 (butyl acetate = 1)				
LOWER FLAMMABILITY LIMIT	3.3% V/V for 100% Ethanol, 7.3% V/V for 100% Methanol				
UPPER FLAMMABILITY LIMIT	19 % V/V for 100% Ethanol, 36 % V/V for 100% Methanol				
VAPOR PRESSURE	44 mm Hg @ 20 deg. C, for 100% Ethanol				
VAPOUR DENSITY	1.56 (air=1)				
RELATIVE DENSITY (LIQUID)	0.8085 @ 20°C				
SOLUBILITY IN WATER	Complete				
SOLUBILITY IN OIL- COEFFICIENT	Separates from oil				
OF WATER/OIL DISTRIBUTION					
PARTITION COEFFICIENT	0.032 approx.				
N- OCTANOL/ WATER					
AUTO- IGNITION TEMPERATURE	Approx. 370 deg. C				
DECOMPOSITION TEMPERATURE	Specific data not available				
VISCOSITY	Approx. 1.35 cp @ 20 deg. C				
% VOLATILES BY VOLUME	100				
CHEMICAL FORMULA	Ethanol: C2-H5-OHMolecular weight: 46.07Methanol: C-H3-OHMolecular weight: 32.04Water: H2OMolecular weight :18.02				

SECTION 10- STABILITY AND REACTIVITY

CHEMICAL STABILITY/ REACTIVITY	Stable
CONDITIONS TO AVOID	Sources of ignition
POSSIBILITY OF HAZARDOUS REACTIONS/ INCOMPATIBILITIES	Oxidizing materials
HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS	Burning can produce carbon monoxide and/or carbon dioxide and/or formaldehyde.
HAZARDOUS POLYMERIZATION	Will not occur
CONDITIONS TO AVOID	None currently known



PRODUCT NAME: MSDS NO:

Г

SDAG-2 (95%) 2161

PAGE 6 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 11- TOXICOLOGICAL INFORMATION

Г		~~~		1050 (4)	1050 //	1050 //	7
-	INGREDIENT	% V/V	TLV, ppm	LC50, ppm/4h.	LD50, mg/kg	LD50, mg/kg	_
 	(1) F +b-d Alb-d	06.4	1000	RAT, INHAL.	RAT, ORAL	RABBIT, SKIN	-
	(1) Ethyl Alcohol	86.4	1000	31,623	7,060	20,000	-
-	(2) Methanol	9.1	200	64,000	5,628	20,000	_
	Water	Balance	NA	NA	NA	NA	
REFERENCES:	ACGIH (1988-1989),	RTECS (1983).					
INGESTION	 This product contains 4.8% v/v of methanol, a toxic substance known to have caused blindness and death. Following ingestion of SDAG-1 (95%), the symptoms include dizziness, faintness, drowsiness, decreased awareness and responsiveness, euphoria, abdominal discomfort, nausea, vomiting, staggering gait, lack of coordination and coma. 						
SKIN ABSORPTIC		ol can be abso poses little ris	_	h the skin in toxi ect.	ic and lethal am	nounts.	
INHALATION	 High vapour concentrations may cause a burning sensation in the throat and nose, stinging and watering in the eyes. At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting may occur. 						
<u>Skin</u> Contact	-	 Mild irritant. Repeated or prolonged exposure may lead to dermatitis, erythema and scaling. 					
<u>eye</u> <u>Contact</u>	 Vapours Eye dan a few da 	 Severe eye irritant. Vapours can irritate eyes. Eye damage from contact with liquid is reversible and proper treatment will result in healing within a few days. Damage is usually mild to moderate conjunctivitis, seen mainly as redness of the conjunctiva. 					
EFFECTS OF LOI	NG— injury w	ith fibrosis.				evelopment of pro	
		a and impaired				, , , , , ,	
MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE	Y	ed exposure to	ethanol ma	y exacerbate live	er injury produc	ed from other ca	iuses.
OTHER- REPRODU TOXICITY OF ETHA WHEN CONSUMEI BEVERAGE DURIN PREGNANCY	NOL during p D AS A	has been ider pregnancy.	ntified in stuc	lies as a develop	mental toxican	t when consume	ed as a beverage



Product Name: MSDS NO:

SDAG-2 (95%) 2161 PAGE 7 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 12- ECOLOGICAL INFORMATION

Ethyl Alcohol CAS 64-17-5

Ecotoxicity (aquatic and terrestrial, where available): Acute Fish toxicity (ETHANOL) LC50 / 96 HOUR Oncorhynchus mykiss (rainbow trout) > 10,000 mg/l

LC50 / 96 HOUR Pimephales promelas (fathead minnow) > 13,400 mg/l

Toxicity to aquatic plants (ETHANOL)

Growth inhibition / 96 HOURS Chlorella vulgaris (Fresh water algae) 1,000 mg/l

Toxicity to microorganisms (ETHANOL)

Toxicity Threshold / Pseudomonas putida 6,500 mg/l Summary: Inhibition of cell multiplication begins.

Persistence and degradability: Biodegradation is expected.

Bioaccumulative potential: Biaccumulation is unlikely

Other adverse effects: BOD: 740-840 mg/g

Methyl Alcohol 67-56-1

Ecotoxicity (aquatic and terrestrial, where available): Acute Fish Toxicity (METHANOL) LC50 / 96 hours Lepomis macrocirus: 15,400 mg/L / LC50 / 96 hours Fathead minnow: 29,400 mg/L

Toxicity to Aquatic Plants (METHANOL) EC50 / 96 hours Scenedesmus capricornutum: 22,000 mg/L

Toxicity to daphnia and other aquatic invertebrates EC50/ 48 hours / Water flea - > 10,000.00 mg/L

Persistence and degradability: 72% - Readily biodegradable.

Bioaccumulative potential: Bioaccumulation: Carp / 72d / BCF: 1.0

Other adverse effects: BOD: 600 mg/g - 1120 mg/g COD: 1420 mg/g



PRODUCT NAME: MSDS NO: SDAG-2 (95%) 2161

PAGE 8 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 13- DISPOSAL CONSIDERATIONS

<u>Spill</u>	 Contain spilled material. Provide adequate ventilation and protective equipment. Remove sources of heat, sparks or flames. Spill should be collected in suitable containers or absorbed on a suitable absorbent material for subsequent disposal.
WASTE DISPOSAL	• Waste material should be disposed of in an approved incinerator or in a designated landfill site, in compliance with all federal, provincial and local government regulations.

SECTION 14- TRANSPORT INFORMATION

CANADA: UN number: 1987 UN proper shipping name Alcohols, Flammable, N.O.S. (ETHANOL) Transport hazard class(es) Primary Class 3 Packing group (*if applicable*) II

IMDG

UN-Number: UN1987 Class: 3 Packing Group: II EMS-No: F-E, S-D Proper shipping name: ALCOHOLS, N.O.S. (ETHANOL, METHANOL) Marine pollutant: No IATA UN-Number: 1987 Class: 3 Packing Group: II Proper shipping name: Alcohols, N.O.S. (ethanol, methanol)

SECTION 15- REGULATORY INFORMATION

All ingredients are on the following inventories or are exempted from listing:

Country Notification

Australia AICS Canada DSL China IECS **European Union EINECS** ENCS/ISHL Japan Korea ECL New Zealand NZIOC Philippines PICCS USA TSCA

California Prop 65 Components

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm when drunk as a beverage: (ETHYL ALCOHOL) CAS No. 64-17-5 Revision Date: December 11, 2009

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. METHANOL CAS-No. 67-56-1 Revision Date 2012-03-16



PRODUCT NAME: SDAG-2 (95%) MSDS NO: 2161

PAGE 9 OF 9 EFFECTIVE DATE: February 14, 2018

SECTION 16- OTHER INFORMATION

PREPARED BY: Alcohol QA, Technical Services, and Regulatory Affairs Department

PHONE NUMBER: (905) 790-7500



GREENFIELD GLOBAL URGES EACH CUSTOMER OR RECIPIENT OF THIS SDS TO STUDY IT CAREFULLY TO BECOME AWARE OF AND UNDERSTAND THE HAZARDS ASSOCIATED WITH THE PRODUCT. THE READER SHOULD CONSIDER CONSULTING REFERENCE WORKS OR INDIVIDUALS WHO ARE EXPERTS IN VENTILATION, TOXICOLOGY OR FIRE PREVENTION, AS NECESSARY OR APPROPRIATE TO USE AND UNDERSTAND THE DATA CONTAINED IN THIS MSDS.

TO PROMOTE SAFE USE AND HANDLING OF THIS PRODUCT, EACH CUSTOMER OR RECIPIENT SHOULD (1) NOTIFY EMPLOYEES, AGENTS, CONTRACTORS AND OTHERS WHO MAY USE THIS MATERIAL, OF THE INFORMATION IN THIS MSDS AND ANY OTHER INFORMATION REGARDING HAZARDS OR SAFETY, (2) FURNISH THIS SAME INFORMATION TO EACH CUSTOMER FOR THE PRODUCT, AND (3) REQUEST CUSTOMERS TO NOTIFY THEIR EMPLOYEES, CUSTOMERS, AND OTHER USERS OF THE PRODUCT OF THIS INFORMATION.