# GREENFIELD

# SAFETY DATA SHEET

## 1. Identification

Product identifier SDA 40-B, 200 Proof

Other means of identification None.

**Recommended use**General purpose solvent.

**Recommended restrictions**Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

Company nameGreenfield Global Inc.Address6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

**Telephone** (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CHEMTREC: 1-800-424-9300

## 2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide to extinguish.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

# 3. Composition/information on ingredients

## **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	99.87
Other components below reportable levels			0.13

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

## **Environmental precautions**

7. Handling and storage Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective

SDA 40-B, 200 Proof SDS Canada

equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

# 8. Exposure controls/personal protection

Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Oc	cupational Health & Safety Code, Sche	dule 1, Table 2)
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
		for Chemical Substances, Occupational Health and
Safety Regulation 296/97, Components	as amended) Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
,	Reg. 217/2006, The Workplace Safety A	••
Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (C	ontrol of Exposure to Biological or Che	mical Agents)
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (M	linistry of Labor - Regulation respecting	g occupational health and safety)
Components	Туре	Value
	T\A/A	
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3 1000 ppm
,	TWA ELs (Occupational Health and Safety Ro	1000 ppm
,		1000 ppm
Canada. Saskatchewan O	ELs (Occupational Health and Safety Ro	1000 ppm egulations, 1996, Table 21)
Canada. Saskatchewan O	ELs (Occupational Health and Safety Ro Type	1000 ppm egulations, 1996, Table 21) Value
Canada. Saskatchewan O	ELs (Occupational Health and Safety Re Type 15 minute	1000 ppm egulations, 1996, Table 21) Value  1250 ppm 1000 ppm
Canada. Saskatchewan Ol Components Ethanol (CAS 64-17-5)	ELs (Occupational Health and Safety Ro Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeric	1000 ppm  egulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used o conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an
Canada. Saskatchewan Ol Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering	ELs (Occupational Health and Safety Ro Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash sta	1000 ppm  egulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommender not been established, maintain airborne levels to an attion and safety shower.
Canada. Saskatchewan Ol Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering	ELs (Occupational Health and Safety Ro Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash sta	1000 ppm  egulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used o conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an attion and safety shower.
Canada. Saskatchewan Ole Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols	ELs (Occupational Health and Safety ReType  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields	1000 ppm  egulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, local or good controls to maintain airborne levels below recommended on the enclosure of the enclos
Canada. Saskatchewan Ole Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  ividual protection measure Eye/face protection	ELs (Occupational Health and Safety ReType  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields  Butyl rubber or Viton® gloves are reco	1000 ppm  egulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, local or good controls to maintain airborne levels below recommended on the enclosure of the enclos
Canada. Saskatchewan Ole Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  ividual protection measure Eye/face protection  Skin protection	ELs (Occupational Health and Safety ReType  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields  Butyl rubber or Viton® gloves are received the glove supplier. Be aware that the limits and safety glasses with side shields	1000 ppm  Pegulations, 1996, Table 21) Value  1250 ppm 1000 ppm  The ingredient(s).  Paust ventilation. Good general ventilation should be used a conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommended not been established, maintain airborne levels to an attion and safety shower.  Pent (or goggles). Chemical goggles are recommended.  Pent (or goggles). Chemical goggles can be recommended be iquid may penetrate the gloves. Frequent change is
Canada. Saskatchewan Of Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  ividual protection measure Eye/face protection  Skin protection  Hand protection	ELs (Occupational Health and Safety ReType  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields  Butyl rubber or Viton® gloves are received the glove supplier. Be aware that the ladvisable.  Wear appropriate chemical resistant of lengineering controls do not maintain	aust ventilation. Good general ventilation should be used o conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an ation and safety shower.  International goggles are recommended.  International goggles are recommended being and penetrate the gloves. Frequent change is allothing.  In airborne concentrations below recommended exposure ptable level (in countries where exposure limits have not
Canada. Saskatchewan Of Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  ividual protection measure Eye/face protection  Skin protection  Hand protection  Other	Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields  Butyl rubber or Viton® gloves are receptated the glove supplier. Be aware that the ladvisable.  Wear appropriate chemical resistant of light for the glove of t	agulations, 1996, Table 21) Value  1250 ppm 1000 ppm  the ingredient(s).  aust ventilation. Good general ventilation should be used a conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommended in an established, maintain airborne levels to an action and safety shower.  Int (or goggles). Chemical goggles are recommended.  Immended. Other suitable gloves can be recommended in a goggles are recommended.  Immended. Other suitable gloves. Frequent change is a lothing.  In airborne concentrations below recommended exposure ptable level (in countries where exposure limits have not ator must be worn.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. Form Liquid.

Colour Clear liquid; invisible vapour.

Odour Alcoholic.

Odour threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling 7

78.3 - 80 °C (172.94 - 176 °F)

range

Flash point 13 °C (55.4 °F) Closed cup

Evaporation rate Expected to be rapid

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits Explosive limit - lower (%) 3.3 % v/v (f

**Explosive limit - lower (%)** 3.3 % v/v (for Ethanol) **Explosive limit - upper** 19 % v/v (for Ethanol)

(%)

Vapour pressure 44.6 mm Hg (20 °C (68 °F) (for Ethanol))

**Vapour density** 1.4 - 1.6 (air=1.0)

**Relative density** 0.796 - 0.881 g/ml (25 °C (77 °F))

Solubility(ies)

Solubility (water) Complete

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperature

363 °C (685.4 °F) Ethanol

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Explosive properties** Not explosive. **Oxidising properties** Not oxidising.

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact**No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing.

## Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components Species Test Results

Ethanol (CAS 64-17-5)

Acute Inhalation

Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

Serious eye damage/eye

Prolonged skin contact may cause temporary irritation. Causes serious eye irritation.

Respiratory or skin sensitisation

**Respiratory sensitisation** Not a respiratory sensitiser.

**Skin sensitisation** This product is not expected to cause skin sensitisation.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Ethanol (CAS 64-17-5)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Ethanol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours

SDA 40-B, 200 Proof SDS Canada

959316 Version #: 02 Revision date: - 13-December-2023 Issue date: 30-August-2021

**Test Results** Components **Species** NOEC 280 mg/l, 7 days Other Lemna minor Other Acute LC50 Micro-organisms Micro-organisms 5800 mg/l, 4 hours **Terrestrial** Acute Plant EC50 Terrestrial plant 633 mg/kg dw

Persistence and degradability

Expected to be readily biodegradable.

Bioaccumulative potential

The product is not expected to bioaccumulate.

Mobility in soil

Expected to be mobile in soil.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

## 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

#### **TDG**

**UN** number UN1987

**UN proper shipping name** 

ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

**Class** 3 Subsidiary risk Ш Packing group **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN1987 **UN** number

**UN proper shipping name** 

Alcohols, n.o.s. (Ethanol)

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** Nο **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN number** UN1987

UN proper shipping name

Transport hazard class(es)

ALCOHOLS, N.O.S. (Ethanol)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** 

> Marine pollutant No. F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This product is not intended to be transported in bulk.

## 15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

## **Controlled Drugs and Substances Act**

Not regulated.

## Export Control List (CEPA 1999, Schedule 3)

Inventory name

Not listed.

#### **Greenhouse Gases**

Not listed.

#### **Precursor Control Regulations**

Not regulated.

## International regulations

#### Stockholm Convention

Not applicable.

## **Rotterdam Convention**

Not applicable.

## **Kyoto Protocol**

Not applicable.

#### **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

Country(s) or region

## **International Inventories**

Australia

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Australian Inventory of Industrial Chemicals (AICIS)

## 16. Other information

Issue date30-August-2021Revision date13-December-2023

Version No. 02

SDA 40-B, 200 Proof SDS Canada

On inventory (yes/no)\*

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.