SAFETY DATA SHEET



1. Identification

Product identifier Calsol 100

Other means of identification

Synonyms Proprietary denatured alcohol formulation Calsol 100

Recommended use Transfer fluid for ground source heat systems

Recommended restrictions Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

Company name Greenfield Global Inc.

Address 6985 Financial Drive

Mississauga, Ontario

L5N 0G3Canada

Telephone (905) 790-7500

Website http://www.greenfield.com

24-Hour Emergency CHEMTREC: 1-800-424-9300

Contact

2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide. to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	90 - < 93
Other components below reportable levels			7 - < 10

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Calsol 100 SDS Canada

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eve contact

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. Combustion products may include: Carbon oxides.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Use water spray to keep fire-exposed

Fire fighting equipment/instructions

containers cool.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Calsol 100 SDS Canada Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Осси	national	exposure	limits
Occu	pational	exposure	111111113

Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (O	ccupational Health & Safety Code, Sche	dule 1, Table 2)
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. British Columbia Safety Regulation 296/97,		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety A	nd Health Act)
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (C	control of Exposure to Biological or Che	mical Agents)
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (N	/linistry of Labor - Regulation respecting Туре	g occupational health and safety) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3 1000 ppm
,	TWA ELs (Occupational Health and Safety Re Type	1000 ppm
Canada. Saskatchewan O	ELs (Occupational Health and Safety Re	1000 ppm egulations, 1996, Table 21)
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety Ro Type	1000 ppm egulations, 1996, Table 21) Value
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5)	ELs (Occupational Health and Safety Ro Type 15 minute 8 hour	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm
Canada. Saskatchewan O Components	PELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeric	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used a conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeric exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipments.	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used o conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to antition and safety shower.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols ividual protection measure Eye/face protection Skin protection	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, local ong controls to maintain airborne levels below recommender not been established, maintain airborne levels to an auton and safety shower. ent (or goggles). Chemical goggles are recommended.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols ividual protection measure Eye/face protection	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant g	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an antion and safety shower. ent (or goggles). Chemical goggles are recommended.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols ividual protection measure Eye/face protection Skin protection	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant g	1000 ppm Pegulations, 1996, Table 21) Value 1250 ppm 1000 ppm The ingredient(s). Paust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommended not been established, maintain airborne levels to an antion and safety shower. Pent (or goggles). Chemical goggles are recommended. Roves. Suitable gloves can be recommended by the glove penetrate the gloves. Frequent change is advisable.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols ividual protection measure Eye/face protection Skin protection Hand protection	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant graphics. Be aware that the liquid may wear appropriate chemical resistant of the figure of the first supplier. Be aware that the liquid may wear appropriate chemical resistant of the figure of the figure applicable) or to an acceptable or to an acce	agulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used of conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommended enot been established, maintain airborne levels to an attion and safety shower. Int (or goggles). Chemical goggles are recommended. Iloves. Suitable gloves can be recommended by the glove penetrate the gloves. Frequent change is advisable. Ilothing. I airborne concentrations below recommended exposure ptable level (in countries where exposure limits have not
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols ividual protection measure Eye/face protection Skin protection Hand protection Other	Type 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits have acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant group supplier. Be aware that the liquid may wear appropriate chemical resistant of the engineering controls do not maintain	agulations, 1996, Table 21) Value 1250 ppm 1000 ppm the ingredient(s). aust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, localing controls to maintain airborne levels below recommender not been established, maintain airborne levels to an antion and safety shower. Int (or goggles). Chemical goggles are recommended. Iloves. Suitable gloves can be recommended by the glove penetrate the gloves. Frequent change is advisable. Ilothing. In airborne concentrations below recommended exposure ptable level (in countries where exposure limits have not ator must be worn.

Calsol 100 SDS Canada

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Colour Blue-purple.
Odour Alcoholic.
Odour threshold Not available.
pH Not available.

Melting point/freezing point -100 °C (-148 °F) estimated

Initial boiling point and boiling 78.3 - 100 °C (172.94 - 212 °F) estimated

range

Flash point 16 °C (60.8 °F) Closed cup (ASTM D-56)

Evaporation rate 1.7 (Butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 3.3 % v/v (for 100% Ethanol) **Explosive limit - upper** 19 % v/v (for 100% Ethanol)

(%)

Vapour pressure 44 mm Hg (for 100% Ethanol) (20 °C (68 °F))

Vapour density 1.56 (Air=1)
Solubility(ies) Complete

Solubility (water) 0.032 estimated

Partition coefficient (n-octanol/water)

Auto-ignition temperature

Decomposition temperature 370 °C (698 °F) estimated

Viscosity Not available.

Other information 1.35 cP (20 °C (68 °F))

Explosive properties Not explosive.

Oxidising properties Not oxidising.

Percent volatile 100 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Calsol 100 SDS Canada

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species **Test Results** Ethanol (CAS 64-17-5)

Acute Inhalation Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eve damage/eve

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

This product is not expected to cause skin sensitisation. Skin sensitisation

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Ethanol (CAS 64-17-5) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Ethanol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Ethanol (CAS 64-17-5) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Ethanol (CAS 64-17-5) Aquatic Acute EC₁₀ Algae Freshwater algae 11.5 mg/l, 72 hours EC50 Freshwater algae 275 mg/l, 72 hours Marine water algae 1900 mg/l Fish LC50 Freshwater fish 11200 mg/l, 24 hours Invertebrate EC50 Freshwater invertebrate 5012 mg/l, 48 hours Marine water invertebrate 857 mg/l, 48 hours Other EC50 Lemna minor 4432 mg/l, 7 days

Calsol 100 SDS Canada

	Species	Test Results	
NOEC	Marine water algae	1580 mg/l	
NOEC	Freshwater fish	250 mg/l	
NOEC	Freshwater invertebrate	9.6 mg/l, 10 days	
	Marine water invertebrate	79 mg/l, 96 hours	
NOEC	Lemna minor	280 mg/l, 7 days	
LC50	Micro-organisms	5800 mg/l, 4 hours	
EC50	Terrestrial plant	633 mg/kg dw	
	NOEC NOEC NOEC	NOEC Marine water algae NOEC Freshwater fish NOEC Freshwater invertebrate Marine water invertebrate NOEC Lemna minor LC50 Micro-organisms	NOEC Marine water algae 1580 mg/l NOEC Freshwater fish 250 mg/l NOEC Freshwater invertebrate 9.6 mg/l, 10 days Marine water invertebrate 79 mg/l, 96 hours NOEC Lemna minor 280 mg/l, 7 days LC50 Micro-organisms 5800 mg/l, 4 hours

Persistence and degradability

Expected to be readily biodegradable.

Bioaccumulative potential

The product is not expected to bioaccumulate.

Partition coefficient n-octanol / water (log Kow)

Calsol 100 0.032 Estimated

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN1987 **UN number**

UN proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1987

UN proper shipping name Alcohols, n.o.s. (Ethanol)

Transport hazard class(es)

3 **Class** Subsidiary risk П Packing group **Environmental hazards** No. 3L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

960048

UN number UN1987

ALCOHOLS, N.O.S. (Ethanol) **UN proper shipping name**

Version #: 03 Revision date: 1-November-2023

Calsol 100 SDS Canada

Issue date: 09-December-2021

Transport hazard class(es)

3 Class Subsidiary risk П Packing group **Environmental hazards**

Marine pollutant No.

EmS F-E, S-D Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations

contains all the information required by the HPR.

This product is not intended to be transported in bulk.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

Issue date	09-December-2021	
Calsol 100		SDS Canada

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date Version No. Disclaimer 1-November-2023

03

Greenfield Global Commercial Alcohols cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.

Calsol 100 SDS Canada