# SAFETY DATA SHEET



## 1. Identification

Product identifier Calsol 100

Other means of identification

Synonyms Proprietary denatured alcohol formulation Calsol 100

Recommended use Transfer fluid for ground source heat systems

Recommended restrictions Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

**Company name** Greenfield Global Inc. **Address** 6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

**Telephone** (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CANUTEC: (613) 996-6666

#### 2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation.

**Precautionary statement** 

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide. to extinguish.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	90 - < 93
Other components below	reportable levels		7 - < 10

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eve contact

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

delayed

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods General fire hazards Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. Combustion products may include: Carbon oxides.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Use water spray to keep fire-exposed containers cool.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# **Environmental precautions**

# 7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational expos	sure	limits
--------------------	------	--------

Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Oc Components	ccupational Health & Safety Code, Sch Type	edule 1, Table 2) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. British Columbia Safety Regulation 296/97,		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs ( Components	Reg. 217/2006, The Workplace Safety A Type	And Health Act) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (C Components	ontrol of Exposure to Biological or Ch Type	emical Agents) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (M	linistry of Labor - Regulation respectir Type	ng occupational health and safety) Value
	TIA/A	
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3 1000 ppm
, ,	ELs (Occupational Health and Safety F Type	1000 ppm
Canada. Saskatchewan O	ELs (Occupational Health and Safety F	1000 ppm Regulations, 1996, Table 21)
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety F Type	1000 ppm Regulations, 1996, Table 21) Value
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety F Type 15 minute	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s). haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommended by enot been established, maintain airborne levels to an
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer exposure limits. If exposure limits has acceptable level. Provide eyewash sees, such as personal protective equipments.	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s). haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommended to the process of the pr
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer exposure limits. If exposure limits has acceptable level. Provide eyewash sites, such as personal protective equipmer Wear safety glasses with side shields.  Wear appropriate chemical resistant	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s).  haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommended ve not been established, maintain airborne levels to an tation and safety shower.  sent s (or goggles). Chemical goggles are recommended.
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  ividual protection measure Eye/face protection Skin protection	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer exposure limits. If exposure limits has acceptable level. Provide eyewash sites, such as personal protective equipmer Wear safety glasses with side shields.  Wear appropriate chemical resistant	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s). haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommended ve not been established, maintain airborne levels to an lation and safety shower.  Tent  Se (or goggles). Chemical goggles are recommended.  Igloves. Suitable gloves can be recommended by the glove by penetrate the gloves. Frequent change is advisable.
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering itrols  ividual protection measure Eye/face protection Skin protection Hand protection	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer exposure limits. If exposure limits has acceptable level. Provide eyewash sites, such as personal protective equipmed wear safety glasses with side shields.  Wear appropriate chemical resistant supplier. Be aware that the liquid mat wear appropriate chemical resistant If engineering controls do not maintal	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s). haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommendate on the been established, maintain airborne levels to an tation and safety shower.  The sent of the gloves can be recommended by the glove of the gloves. Suitable gloves can be recommended by the glove of the gloves. Frequent change is advisable. In airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not
Canada. Saskatchewan O Components  Ethanol (CAS 64-17-5)  logical limit values propriate engineering atrols  evidual protection measure Eye/face protection Skin protection Hand protection Other	ELs (Occupational Health and Safety F Type  15 minute 8 hour  No biological exposure limits noted for Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other engineer exposure limits. If exposure limits has acceptable level. Provide eyewash sites, such as personal protective equipmed Wear safety glasses with side shields.  Wear appropriate chemical resistant supplier. Be aware that the liquid mat wear appropriate chemical resistant of the significant of the supplication of the safety glasses with side shields.	1000 ppm  Regulations, 1996, Table 21) Value  1250 ppm 1000 ppm  or the ingredient(s). haust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ring controls to maintain airborne levels below recommended we not been established, maintain airborne levels to an tation and safety shower.  Itent  Se (or goggles). Chemical goggles are recommended.  Gloves. Suitable gloves can be recommended by the glove by penetrate the gloves. Frequent change is advisable.  Clothing.  In airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not irrator must be worn.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.
Colour Blue-purple.
Odour Alcoholic.
Odour threshold Not available.
pH Not available.

Melting point/freezing point -100 °C (-148 °F) estimated

Initial boiling point and boiling 78.3 - 100 °C (172.94 - 212 °F) estimated

range

Flash point 16 °C (60.8 °F) Closed cup (ASTM D-56)

**Evaporation rate** 1.7 (Butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 3.3 % v/v (for 100% Ethanol)

Explosive limit - upper 19 % v/v (for 100% Ethanol)

(%)

Vapour pressure 44 mm Hg (for 100% Ethanol) (20 °C (68 °F))

Vapour density 1.56 (Air=1)

**Relative density** 0.81 - 0.816 (20 °C (68 °F))

Solubility(ies)

Solubility (water) Complete

Partition coefficient 0.032 estimated

(n-octanol/water)

Auto-ignition temperature 370 °C (698 °F) estimated

**Decomposition temperature** Not available.

**Viscosity** 1.35 cP (20 °C (68 °F))

Other information

Explosive properties Not explosive.

Oxidising properties Not oxidising.

Percent volatile 100 %

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

## Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components **Species Test Results** Ethanol (CAS 64-17-5)

Acute Inhalation Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eve damage/eve

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Ethanol (CAS 64-17-5) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Ethanol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Ethanol (CAS 64-17-5) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Ethanol (CAS 64-17-5) Aquatic Acute EC<sub>10</sub> Algae Freshwater algae 11.5 mg/l, 72 hours EC50 Freshwater algae 275 mg/l, 72 hours Marine water algae 1900 mg/l Fish LC50 Freshwater fish 11200 mg/l, 24 hours Invertebrate EC50 Freshwater invertebrate 5012 mg/l, 48 hours Marine water invertebrate 857 mg/l, 48 hours Other EC50 Lemna minor 4432 mg/l, 7 days

Components		Species	Test Results	
Chronic				
Algae	NOEC	Marine water algae	1580 mg/l	
Fish	NOEC	Freshwater fish	250 mg/l	
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days	
		Marine water invertebrate	79 mg/l, 96 hours	
Other	NOEC	Lemna minor	280 mg/l, 7 days	
Other				
Acute				
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours	
Terrestrial				
Acute				
Plant	EC50	Terrestrial plant	633 mg/kg dw	

Persistence and degradability

Expected to be readily biodegradable.

The product is not expected to bioaccumulate. Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Calsol 100 0.032 Estimated

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

**TDG** 

UN1987 **UN number** 

**UN** proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IATA** 

**UN** number UN1987

**UN** proper shipping name Alcohols, n.o.s. (Ethanol)

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** No. 3L **ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN number** UN1987

ALCOHOLS, N.O.S. (Ethanol) **UN proper shipping name** 

Transport hazard class(es)

Class 3 Subsidiary risk -Packing group II

**Environmental hazards** 

Marine pollutant No. EmS F-E, S-D

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

This product is not intended to be transported in bulk.

## **Controlled Drugs and Substances Act**

Not regulated.

## Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### **Greenhouse Gases**

Not listed.

## **Precursor Control Regulations**

Not regulated.

## International regulations

## **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

## **Kyoto Protocol**

Not applicable.

### **Montreal Protocol**

Not applicable.

## **Basel Convention**

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

## 16. Other information

United States & Puerto Rico

Issue date 09-D6	cember-2021

Calsol 100 SDS Canada

No

Revision date Version No. Disclaimer

01

Greenfield Global Commercial Alcohols cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.