GREENFIELD

SAFETY DATA SHEET

1. Identification

Product identifier Isopropyl Alcohol, 70%

Other means of identification

Synonyms Isopropanol, 2-Propanol, Dimethyl carbinol, IPA

Recommended use Rubbing alcohol. General purpose solvent.

Recommended restrictions Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

Company name Greenfield Global Inc. **Address** 6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

Telephone (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CHEMTREC: 1-800-424-9300

2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity following single Category 3 narcotic effects

exposure

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF

INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol resistant foam, dry chemical

powder, carbon dioxide to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Skin contact

Chemical name	Common name and synonyms	CAS number	%
Isopropyl alcohol		67-63-0	62.73
Other components below	reportable levels		37.27

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Valս Components	Туре	Value
Isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm
,	TWA	200 ppm
Canada. Alberta OELs (Occupat	ional Health & Safety Code, Sche	dule 1, Table 2)
Components	Туре	Value
Isopropyl alcohol (CAS 67-63-0)	STEL	984 mg/m3
		400 ppm
	TWA	492 mg/m3
		200 ppm
Canada. British Columbia OELs Safety Regulation 296/97, as am		for Chemical Substances, Occupational Health and
Components	Туре	Value
Isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Canada, Manitoba OELs (Reg. 2	17/2006. The Workplace Safety A	nd Health Act)
	17/2006, The Workplace Safety A Type	nd Health Act) Value
Canada. Manitoba OELs (Reg. 2 Components Isopropyl alcohol (CAS 67-63-0)		
Components Isopropyl alcohol (CAS	Туре	Value
Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA	Value 400 ppm 200 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control	Type STEL	Value 400 ppm 200 ppm
Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA of Exposure to Biological or Che	Value 400 ppm 200 ppm mical Agents)
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS	Type STEL TWA of Exposure to Biological or Che Type	Value 400 ppm 200 ppm mical Agents) Value
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA of Exposure to Biological or Che Type STEL TWA	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry	Type STEL TWA of Exposure to Biological or Che Type STEL TWA	Value 400 ppm 200 ppm mical Agents) Value 400 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry Components Isopropyl alcohol (CAS	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry Components Isopropyl alcohol (CAS	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting Type	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm 200 ppm y occupational health and safety) Value
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry Components Isopropyl alcohol (CAS	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting Type	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm 200 ppm 1230 mg/m3
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting Type STEL	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm 200 ppm 1230 mg/m3 500 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting Type STEL Type STEL Type STEL	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm 200 ppm 1230 mg/m3 500 ppm 983 mg/m3 400 ppm
Components Isopropyl alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control Components Isopropyl alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry Components Isopropyl alcohol (CAS 67-63-0)	Type STEL TWA of Exposure to Biological or Che Type STEL TWA y of Labor - Regulation respecting Type STEL	Value 400 ppm 200 ppm mical Agents) Value 400 ppm 200 ppm 200 ppm 200 ppm 1230 mg/m3 500 ppm 983 mg/m3 400 ppm

8 hour

Components Type Value

Biological limit values

ACGIH Biological	Exposure	Indices
------------------	----------	---------

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl alcohol (CAS	40 mg/l	Acetone	Urine	*
67-63-0)				

^{* -} For sampling details, please see the source document.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

200 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Neoprene, butyl rubber, nitrile or Viton® gloves are

recommended. Other suitable gloves can be recommended by the glove supplier. Be aware that

the liquid may penetrate the gloves. Frequent change is advisable.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with

organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Colour Colourless.
Odour Alcohol-like.
Odour threshold Not available.
pH Not available.

Melting point/freezing point -89 °C (-128.2 °F) Approximate Initial boiling point and boiling 81.3 - 83 °C (178.34 - 181.4 °F)

range

Flash point 21.0 °C (69.8 °F) Tag closed cup (ASTM D 56)

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

2.5 % v/v (for Isopropyl Alcohol)

(%)

Flammability limit - upper 12 % v/v (for Isopropyl Alcohol)

(%)

Vapour pressure

4.4 kPa (for Isopropyl Alcohol) (20 °C (68 °F))

Vapour density 2.07 (for Isopropyl Alcohol)

Relative density Not available.

Solubility(ies)

Solubility (water) Complete

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

399 °C (750.2 °F) (for Isopropyl Alcohol)

Decomposition temperature

Explosive properties

Not available. Not available.

Other information

Not explosive.

Oxidising properties
Percent volatile

100 % v/v

10. Stability and reactivity

Reactivity

Viscosity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability
Possibility of hazardous

Conditions to avoid

Material is stable under normal conditions. Hazardous polymerisation does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Hazardous decomposition

Acids. Strong oxidising agents. Chlorine. Isocyanates.

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May c

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results		
sopropyl alcohol (CAS 67-63-0)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	12870 mg/kg		
Inhalation				
Vapour				
LC50	Rat	72.6 mg/l, 4 Hours		
Oral				
LD50	Rat	4710 mg/kg		

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Isopropyl Alcohol, 70% SDS Canada

957777 Version #: 02 Revision date: 12-December-2023 Issue date: 04-May-2021

ACGIH Carcinogens

Isopropyl alcohol (CAS 67-63-0)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Isopropyl alcohol (CAS 67-63-0)

Not classifiable as a human carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Isopropyl alcohol (CAS 67-63-0) Aquatic Acute Crustacea LC50 > 10000 mg/l, 24 hours Daphnia magna Fish LC50 Pimephales promelas 9640 mg/l, 96 hours

Chronic

Crustacea EC50 Daphnia magna Daphnia magna > 100 mg/l, 21 days

141 mg/l, 16 days 30 mg/l, 21 days

Persistence and degradability

Expected to be readily biodegradable.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Isopropyl alcohol (CAS 67-63-0)

0.05

Mobility in soil Expected to be highly mobile in soil.

NOEC

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Contaminated packaging

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN1219

UN proper shipping name

ISOPROPANOL

Transport hazard class(es) Class 3 Subsidiary risk

Ш Packing group **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1219
UN proper shipping name Isopropanol

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1219
UN proper shipping name ISOPROPANOL

Transport hazard class(es)

Class 3
Subsidiary risk Packing group || Environmental hazards

Marine pollutant No. EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

This product is not intended to be transported in bulk.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable. Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or regionInventory nameOn inventory (yes/no)*JapanInventory of Existing and New Chemical Substances (ENCS)YesKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information

Issue date04-May-2021Revision date12-December-2023

Version No.

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all

necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).