G COPENIES D

SAFETY DATA SHEET

1. Identification

Product identifier SDA 40-B, 190 Proof

Other means of identification None.

Recommended use General purpose solvent.

Recommended restrictions Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

Company nameGreenfield Global Inc.Address6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

Telephone (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CHEMTREC: 1-800-424-9300

2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	92.31
Other components below reportable levels			7.69

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods
General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Осси	national	exposure	limits
Occu	pational	exposure	111111113

Components	nit Values Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
,	ccupational Health & Safety Code, Sche	• •
Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. British Columbia	OELs. (Occupational Exposure Limits	for Chemical Substances, Occupational Health and
Safety Regulation 296/97,	•	Value
Components	Type	
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs (Components	Reg. 217/2006, The Workplace Safety A Type	nd Health Act) Value
	STEL	
Ethanol (CAS 64-17-5)		1000 ppm
Canada. Ontario OELs. (C Components	Control of Exposure to Biological or Che Type	emical Agents) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
,	######################################	• •
Components	Type	Value
	T\\/ \	1880 mg/m3
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Ethanol (CAS 64-17-5)	IVVA	1000 ppm
,	ELs (Occupational Health and Safety R	1000 ppm
,		1000 ppm
Canada. Saskatchewan O	ELs (Occupational Health and Safety R	1000 ppm egulations, 1996, Table 21)
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety Ro Type	1000 ppm egulations, 1996, Table 21) Value
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety Ro Type 15 minute	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5)	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende not been established, maintain airborne levels to an
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipments.	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender not been established, maintain airborne levels to an action and safety shower.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipments.	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used. to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender the not been established, maintain airborne levels to an ation and safety shower.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols evidual protection measure Eye/face protection	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant of	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommend the not been established, maintain airborne levels to an ation and safety shower. ent (or goggles). Chemical goggles are recommended.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering itrols ividual protection measure Eye/face protection Skin protection	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant of	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommend e not been established, maintain airborne levels to an ation and safety shower. ent (or goggles). Chemical goggles are recommended.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering itrols ividual protection measure Eye/face protection Skin protection Hand protection	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant of supplier. Be aware that the liquid may Wear appropriate chemical resistant of the figure of the figure of the resistant of the figure of the resistant	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommend to not been established, maintain airborne levels to an ation and safety shower. ent (or goggles). Chemical goggles are recommended. gloves. Suitable gloves can be recommended by the glover penetrate the gloves. Frequent change is advisable. clothing. n airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering atrols ividual protection measure Eye/face protection Skin protection Hand protection Other	ELs (Occupational Health and Safety ReType 15 minute 8 hour No biological exposure limits noted for Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash states, such as personal protective equipmed Wear safety glasses with side shields Wear appropriate chemical resistant of supplier. Be aware that the liquid may Wear appropriate chemical resistant of the figure of the supplier of th	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used to conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommend te not been established, maintain airborne levels to an ation and safety shower. ent (or goggles). Chemical goggles are recommended. gloves. Suitable gloves can be recommended by the glove of penetrate the gloves. Frequent change is advisable. clothing. In airborne concentrations below recommended exposure exptable level (in countries where exposure limits have not reator must be worn.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Colour Clear liquid; invisible vapour.

Odour Alcoholic.

Odour threshold Not available.
pH Not available.

Melting point/freezing point -114 - -46 °C (-173.2 - -50.8 °F) Initial boiling point and boiling 78.3 - 80 °C (172.94 - 176 °F)

range

Flash point 16 °C (60.8 °F) Closed cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 3.3 (for Ethanol)
Explosive limit - upper 19 (for Ethanol)

(%)

Vapour pressure 44.6 mm Hg (20 °C (68 °F))

Vapour density 1.4 - 1.6 (air=1.0)

Relative density 0.796 - 0.881 (25 °C (77 °F))

Solubility(ies)

Solubility (water) Complete

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperature 363 °C (685.4 °F) (for Ethanol)

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. **Oxidising properties** Not oxidising.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactNo adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

Ethanol (CAS 64-17-5)

Acute Inhalation

Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

Prolonged skin contact may cause temporary irritation. Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

irritation

ACGIH Carcinogens

Ethanol (CAS 64-17-5)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Ethanol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours

SDA 40-B, 190 Proof SDS Canada

959333 Version #: 02 Revision date: 13-December-2023 Issue date: 30-August-2021

Components **Species Test Results** NOEC 280 mg/l, 7 days Other Lemna minor Other Acute LC50 Micro-organisms Micro-organisms 5800 mg/l, 4 hours **Terrestrial** Acute Plant EC50 Terrestrial plant 633 mg/kg dw

Persistence and degradability

The product is expected to be biodegradable.

The product is not expected to bioaccumulate.

Mobility in soil Expected to be mobile in soil.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN1987

UN proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1987

UN proper shipping name Alcohols, n.o.s. (Ethanol)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1987

UN proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This product is not intended to be transported in bulk.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Inventory name

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Country(s) or region

Not applicable.

International Inventories

Australia

	· · · · · · · · · · · · · · · · · · ·	
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Australian Inventory of Industrial Chemicals (AICIS)

16. Other information

Issue date30-August-2021Revision date13-December-2023

Version No. 02

SDA 40-B, 190 Proof SDS Canada

On inventory (yes/no)*

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.