# SAFETY DATA SHEET



### 1. Identification

Product identifier SDAG-7, 95%

Other means of identification

Synonyms Specially denatured alcohol \* Ethanol denatured with toluene

**Recommended use**General purpose solvent.

**Recommended restrictions**Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency

(Excise) in Canada, US Tax and Trade Bureau in the US, etc.

Manufacturer/Importer/Supplier/Distributor information

**Company name** Greenfield Global Inc. **Address** 6985 Financial Drive

Missisauga, Ontario L5N 0G3

Canada

**Telephone** (905) 790-7500

Website http://www.greenfield.com
Emergency phone number CANUTEC: (613) 996-6666

#### 2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

Reproductive toxicity Category 2

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation. Suspected of damaging fertility

or the unborn child.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant

foam, dry chemical powder, carbon dioxide to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

# 3. Composition/information on ingredients

**Mixtures** 

SDAG-7, 95% SDS Canada

959472 Version #: 01 Revision date: - Issue date: 01-November-2021

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	91.9
Toluene		108-88-3	0.5
Other components below r	eportable levels		7.6

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

**symptoms/effects, acute and** blurred vision. Coughing. **delayed** 

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure

that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing

before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

**Unsuitable extinguishing** Do not use water jet as an extinguisher, as this will spread the fire. **media** 

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions** 

SDAG-7, 95% SDS Canada

959472 Version #: 01 Revision date: - Issue date: 01-November-2021

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

Toluene (CAS 108-88-3)  Canada. Alberta OELs (Occupational Health & Safety Cod Components  Ethanol (CAS 64-17-5)  TWA  Toluene (CAS 108-88-3)  TWA  Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	Value  1880 mg/m3  1000 ppm  188 mg/m3  50 ppm  Limits for Chemical Substances, Occupational Health and
Toluene (CAS 108-88-3)  Canada. Alberta OELs (Occupational Health & Safety Cod Components  Ethanol (CAS 64-17-5)  TWA  Toluene (CAS 108-88-3)  TWA  Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	20 ppm  de, Schedule 1, Table 2) Value  1880 mg/m3 1000 ppm 188 mg/m3 50 ppm  Limits for Chemical Substances, Occupational Health and
Canada. Alberta OELs (Occupational Health & Safety Cod Components Type  Ethanol (CAS 64-17-5) TWA  Toluene (CAS 108-88-3) TWA  Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	de, Schedule 1, Table 2) Value  1880 mg/m3 1000 ppm 188 mg/m3 50 ppm e Limits for Chemical Substances, Occupational Health and
Components  Ethanol (CAS 64-17-5)  TWA  Toluene (CAS 108-88-3)  TWA  Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	Value  1880 mg/m3  1000 ppm  188 mg/m3  50 ppm  Limits for Chemical Substances, Occupational Health and
Toluene (CAS 108-88-3)  Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	1000 ppm  188 mg/m3  50 ppm  Limits for Chemical Substances, Occupational Health and
Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	188 mg/m3 50 ppm Limits for Chemical Substances, Occupational Health and
Canada. British Columbia OELs. (Occupational Exposure Safety Regulation 296/97, as amended)	50 ppm Limits for Chemical Substances, Occupational Health and
Safety Regulation 296/97, as amended)	Limits for Chemical Substances, Occupational Health and
Safety Regulation 296/97, as amended)	
	Volue
Components Type	Value
Ethanol (CAS 64-17-5) STEL	1000 ppm
Toluene (CAS 108-88-3) TWA	20 ppm
Canada. Manitoba OELs (Reg. 217/2006, The Workplace S Components Type	Safety And Health Act)  Value
Ethanol (CAS 64-17-5) STEL	1000 ppm
Toluene (CAS 108-88-3) TWA	20 ppm
Canada. Ontario OELs. (Control of Exposure to Biologica	d or Chemical Agents)
Components Type	Value
Ethanol (CAS 64-17-5) STEL	1000 ppm
Toluene (CAS 108-88-3) TWA	20 ppm
Canada. Quebec OELs. (Ministry of Labor - Regulation res Components Type	specting occupational health and safety)  Value
Ethanol (CAS 64-17-5) TWA	1880 mg/m3
	1000 ppm
Toluene (CAS 108-88-3) TWA	188 mg/m3
	50 ppm
Canada. Saskatchewan OELs (Occupational Health and S Components Type	Safety Regulations, 1996, Table 21) Value
Ethanol (CAS 64-17-5) 15 minute	1250 ppm
8 hour	1000 ppm
Toluene (CAS 108-88-3) 15 minute	60 ppm

Components Type Value

8 hour 50 ppm

## **Biological limit values**

<b>ACGIH Biological</b>	<b>Exposure Indices</b>
-------------------------	-------------------------

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

Canada - Alberta OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Chemical goggles are recommended.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapour cartridge and full facepiece. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other

circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating,

4/9

drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.

**Colour** Clear liquid; invisible vapour.

OdourNot available.Odour thresholdNot available.pHNot available.

Melting point/freezing point  $< -90 \,^{\circ}\text{C} \, (< -130 \,^{\circ}\text{F})$ Initial boiling point and boiling  $78.5 \,^{\circ}\text{C} \, (173.3 \,^{\circ}\text{F})$ 

range

Flash point 13 - 14 °C (55.4 - 57.2 °F) Closed cup

**Evaporation rate** 3 - 3.3 (butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

**Explosive limit - lower (%)** 3.3 % v/v (for 100% Ethyl Alcohol) **Explosive limit - upper** 19 % v/v (for 100% Ethyl Alcohol)

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Completely soluble.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature 363 °C (685.4 °F) (for 100% Ethyl Alcohol)

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Bulk density** 6.61 - 6.8 lb/gal (15.56 °C (60.01 °F))

**Explosive properties** Not explosive. **Oxidising properties** Not oxidising.

10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

Ethanol (CAS 64-17-5)

Acute Inhalation

Vapour

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Components Species Test Results

Toluene (CAS 108-88-3)

Acute Dermal

LD50 Rabbit 12200 mg/kg

Inhalation

Vapour

LC50 Rat 28.1 mg/l, 4 Hours

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

**Skin sensitisation** This product is not expected to cause skin sensitisation.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Ethanol (CAS 64-17-5)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Toluene (CAS 108-88-3) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Ethanol (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

Toluene (CAS 108-88-3)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Ethanol (CAS 64-17-5) Aquatic Acute Algae EC<sub>10</sub> Freshwater algae 11.5 mg/l, 72 hours Freshwater algae 275 mg/l, 72 hours EC50 1900 mg/l Marine water algae Fish LC50 Freshwater fish 11200 mg/l, 24 hours Invertebrate EC50 Freshwater invertebrate 5012 mg/l, 48 hours Marine water invertebrate 857 mg/l, 48 hours Other EC50 Lemna minor 4432 mg/l, 7 days Chronic Algae NOEC Marine water algae 1580 mg/l Fish NOEC Freshwater fish 250 mg/l Invertebrate **NOEC** Freshwater invertebrate 9.6 mg/l, 10 days

Components		Species	Test Results	
		Marine water invertebrate	79 mg/l, 96 hours	
Other	NOEC	Lemna minor	280 mg/l, 7 days	
Other				
Acute				
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours	
Terrestrial				
Acute				
Plant	EC50	Terrestrial plant	633 mg/kg dw	
Toluene (CAS 108-88-3)				
Aquatic				
Acute				
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours	
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours	
Chronic				
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days	
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days	

Persistence and degradability

Expected to be readily biodegradable.

**Bioaccumulative potential** The product is not expected to bioaccumulate.

Partition coefficient n-octanol / water (log Kow)

Toluene (CAS 108-88-3) 2.73

**Mobility in soil** Expected to be mobile in soil.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

TDG

UN number UN1987

UN proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IATA** 

**UN number** UN1987

UN proper shipping name Alcohols, n.o.s. (Ethanol)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.

**ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN1987 **UN** number

ALCOHOLS, N.O.S. (Ethanol) **UN** proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk Ш **Packing group Environmental hazards** 

Marine pollutant No. **EmS** F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

# 15. Regulatory information

**Canadian regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

This product is not intended to be transported in bulk.

### **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### **Greenhouse Gases**

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Toluene (CAS 108-88-3) **Precursor Control Regulations** 

> Toluene (CAS 108-88-3) Class B

# International regulations

### **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

## **Kyoto Protocol**

Not applicable.

## **Montreal Protocol**

Not applicable.

### **Basel Convention**

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

SDAG-7, 95% SDS Canada Country(s) or region Inventory name On inventory (yes/no)\*

Taiwan Chemical Substance Inventory (TCSI)

Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information

Issue date 01-November-2021

Revision date - Version No. 01

Disclaimer

Greenfield Global Commercial Alcohols cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.