

SAFETY DATA SHEET

1. Identification

Product identifier	SDAG-7, Anhydrous		
Other means of identification			
Synonyms	Specially denatured alcohol * Ethanol denatured with toluene * SDA 2B-3 (US equivalent denatured formula)		
Recommended use	General purpose solvent.		
Recommended restrictions	Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in the US, etc.		
Manufacturer/Importer/Supplier/	Distributor information		
Company name	Greenfield Global Inc.		
Address	6985 Financial Drive		
	Missisauga, Ontario L5N 0G3		
	Canada		
Telephone	(905) 790-7500		
Website	http://www.greenfield.com		
Emergency phone number	CHEMTREC: 1-800-424-9300		

2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity	Category 2
Label elements		



Signal word	Danger
Hazard statement	Highly flammable liquid and vapour. Causes serious eye irritation. Suspected of damaging fertility or the unborn child.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental information	None.
Other hazards	None known.

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	99.5
Toluene		108-88-3	0.5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.
6. Accidental release meas	sures
Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.	
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.	
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.	
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.	

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

US. ACGIH Threshold Limit Value Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Canada. Alberta OELs (Occupatio Components	nal Health & Safety Code, Sche Type	dule 1, Table 2) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3
		50 ppm
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Canada. Manitoba OELs (Reg. 217 Components	//2006, The Workplace Safety A Type	nd Health Act) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Canada. Ontario OELs. (Control o Components	f Exposure to Biological or Che Type	mical Agents) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Canada. Quebec OELs. (Ministry o Components	of Labor - Regulation respecting Type	g occupational health and safety) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3
		50 ppm
Canada. Saskatchewan OELs (Oc Components	cupational Health and Safety R Type	egulations, 1996, Table 21) Value
Ethanol (CAS 64-17-5)	15 minute	1250 ppm
	8 hour	1000 ppm
		60 ppm

Canada. Saskatchewan (Components		Type		lue
		8 hour	50	ppm
ological limit values				
ACGIH Biological Expos	ure Indices			
Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
* - For sampling details, pl	ease see the source	document.		
posure guidelines				
Canada - Alberta OELs:	Skin designation			
Toluene (CAS 108-88 Canada - Quebec OELs:	,	Can b	e absorbed throu	gh the skin.
Toluene (CAS 108-88 Canada - Saskatchewan	,		e absorbed throu	gh the skin.
Toluene (CAS 108-88	-3)	Can b	e absorbed throu	gh the skin.
propriate engineering ntrols	Ventilation rate exhaust ventila exposure limits	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommende exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
dividual protection measur	es, such as persor	al protective equipme	ent	
Eye/face protection				emical goggles are recommended.
Skin protection				
Hand protection	Wear appropria supplier. Be av	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.		
Other	Wear appropria	ate chemical resistant c	lothing. Use of ar	n impervious apron is recommended.
Respiratory protection	limits (where a been establish organic vapou is any potentia	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator wit organic vapour cartridge and full facepiece. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.		
Thermal hazards	Wear appropria	ate thermal protective c	lothing, when neo	cessary.
eneral hygiene nsiderations	personal hygie	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Physical and chemica	al properties			
-	· ·			

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Clear liquid; invisible vapour.
Odour	Not available.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	< -90 °C (< -130 °F)
Initial boiling point and boiling range	78.5 °C (173.3 °F)
Flash point	13 - 14 °C (55.4 - 57.2 °F) Closed cup
Evaporation rate	3 - 3.3 (butyl acetate = 1)

SDAG-7, Anhydrous

Flammability (solid, gas)	Not applicable.		
Upper/lower flammability or explosive limits			
Explosive limit - lower (%)	3.3 (for 100% ethyl alcohl)		
Explosive limit – upper (%)	19 (for 100% ethyl alcohl)		
Vapour pressure	Not available.		
Vapour density	Not available.		
Relative density	Not available.		
Solubility(ies)			
Solubility (water)	Completely soluble.		
Partition coefficient (n-octanol/water)	Not available.		
Auto-ignition temperature	363 °C (685.4 °F) (for 100% Ethyl Alcohol)		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Other information			
Bulk density	6.8 lbs/gal (15.56°C/60°F)		
Explosive properties	Not explosive.		
Oxidising properties	Not oxidising.		
10. Stability and reactivity			
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Material is stable under normal conditions.		
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.		
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.		

Incompatible materials	Strong oxidising agents.
Hazardous decomposition	No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.		
Components	Species	Test Results	
Ethanol (CAS 64-17-5)			
<u>Acute</u>			
Inhalation			
Vapour			
LC50	Rat	117 - 125 mg/l, 4 Hours	
Oral			
LD50	Rat	10470 mg/kg	

Components	Species	Test Results	
Toluene (CAS 108-88-3)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	12200 mg/kg	
Inhalation			
Vapour			
LC50	Rat	28.1 mg/l, 4 Hours	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitisation	ı		
Respiratory sensitisation	Not a respiratory sensitiser.		
Skin sensitisation	This product is not expected to cause skin sensitisation.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity			
ACGIH Carcinogens			
Ethanol (CAS 64-17-5)		A3 Confirmed animal carcinogen with unknown relevance to humans.	
Toluene (CAS 108-88-3) Canada - Manitoba OELs: ca	arcinogonicity	A4 Not classifiable as a human carcinogen.	
Ethanol (CAS 64-17-5)	archiogenicity	Confirmed animal carcinogen with unknown relevance to humans	
Toluene (CAS 108-88-3)	Confirmed animal carcinogen with unknown relevance to humans. Not classifiable as a human carcinogen.		
	Evaluation of Carcinogenicity		
Toluene (CAS 108-88-3)		3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Possible reproductive hazard. Suspected of damaging fertility or the unborn child.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be	harmful.	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

		5 1 1	0 0
Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days

Components		Species	Test Results	
		Marine water invertebrate	79 mg/l, 96 hours	
Other	NOEC	Lemna minor	280 mg/l, 7 days	
Other				
Acute				
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours	
Terrestrial				
<i>Acute</i> Plant	EC50	Terrestrial plant	633 mg/kg dw	
Toluene (CAS 108-88-3)	EC30	Terrestilai piant	055 mg/kg uw	
Aquatic				
Acute				
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours	
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours	
Chronic				
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days	
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days	
ersistence and degradability	The produ	ct is not expected to be biodegradable.		
ioaccumulative potential	The produ	The product is not expected to bioaccumulate.		
Partition coefficient n-octa Toluene (CAS 108-88-3)	nol / water (I	og Kow) 2.73		
lobility in soil	Expected	to be mobile in soil.		
ther adverse effects	•	No data available.		
3 Disposal consideratio	ne			
3. Disposal consideratio			re et liegeneed waste die noord eite. Die noor of	
isposal instructions		Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.		
ocal disposal regulations		accordance with all applicable regulation		
azardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
/aste from residues / unused roducts	product re	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
ontaminated packaging		Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or		
4. Transport information	1			
DG				
UN number	UN1987			
UN proper shipping name Transport hazard class(es)		_S, N.O.S. (Ethanol)		
Class	3			
Subsidiary risk	-			
Packing group				
Environmental hazards Special precautions for use	No. er Read safe	ty instructions, SDS and emergency pro	ocedures before handling.	
ATA		,		
UN number	UN1987			
UN proper shipping name Transport hazard class(es)		n.o.s. (Ethanol)		
Class Subsidiary risk	3			
	-			

-11

No.

3L

Subsidiary risk

Environmental hazards

Packing group

ERG Code

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. IMDG

Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes	
New Zealand	New Zealand Inventory	Yes	
Korea	Existing Chemicals List (ECL)	Yes	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
·	Substances (EINECS)		
Europe	European Inventory of Existing Commercial Chemical Yes		
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Canada	Non-Domestic Substances List (NDSL)	No	
Canada	Domestic Substances List (DSL)	Yes	
Country(s) or region Australia	Inventory name Australian Inventory of Industrial Chemicals (AICIS)	On inventory (yes/no)* Yes	
International Inventories		.	
Not applicable.			
Not applicable. Basel Convention			
Not applicable. Montreal Protocol			
Not applicable. Kyoto Protocol			
Rotterdam Convention			
Not applicable.			
Stockholm Convention			
International regulations			
Precursor Control Regulation Toluene (CAS 108-88-3)	ns Class B		
Toluene (CAS 108-88-3)	Foxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)		
Not listed.	Covid Poduction Act 2000 Podulation (55/00 / July 4, 2014)		
Greenhouse Gases			
Not listed.			
Export Control List (CEPA 19	999, Schedule 3)		
Controlled Drugs and Substa Not regulated.	ances Act		
Controlled Drugs and Cub-t	contains all the information required by the HPR.		
15. Regulatory information Canadian regulations	This product has been classified in accordance with the hazard criteria	of the HPR and the SDS	
the IBC Code			
Transport in bulk according to Annex II of MARPOL 73/78 and	Read safety instructions, SDS and emergency procedures before hand Not applicable.	ling.	
EmS	F-E, S-D	1	
Marine pollutant	No.		
Environmental hazards			
Subsidiary risk Packing group	-		
Class	3		
Transport hazard class(es)			
UN proper shipping name	ALCOHOLS, N.O.S. (Ethanol)		
UN number	UN1987		

Country(s) or region

United States & Puerto Rico

Inventory name

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date Revision date Version No. Disclaimer 01-November-2021 19-December-2023

02

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.