

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Special Industrial Ink Solvent Formula SOS 662, 200 Proof  
**Other means of identification** None.  
**Recommended use** General purpose solvent.  
**Recommended restrictions** Use in accordance with supplier's recommendations.

### Manufacturer/Importer/Supplier/Distributor information

**Company Name** Greenfield Global USA Inc.  
**Address** 1101 Isaac Shelby Drive  
 Shelbyville, KY 40065  
 USA  
**Telephone** 502.232.7600  
**Fax** 502.633.6100

**Company Name** Greenfield Global USA Inc.  
**Address** 58 Vale Road  
 Brookfield, CT 06804  
 USA  
**Telephone** 203.740.3471  
**Fax** 203.740.3481

**Emergency phone number**  
**USA** CHEMTREC: 1.800.424.9300 (CCN 17213)  
**International** CHEMTREC: +1.703.527.3887 (CCN 17213)

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2  
**Health hazards** Serious eye damage/eye irritation Category 2  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Highly flammable liquid and vapor. Causes serious eye irritation.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.  
**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.  
**Storage** Store in a well-ventilated place. Keep cool.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Ethyl alcohol	64-17-5	79.5 - 90
Propan-2-ol	67-63-0	5 - 18.05
n-propyl acetate	109-60-4	1
Water	7732-18-5	0 - 5.2

**Composition comments**      All concentrations are in percent by weight unless otherwise indicated.

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is completely soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions****7. Handling and storage****Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm
n-propyl acetate (CAS 109-60-4)	PEL	840 mg/m3
		200 ppm
Propan-2-ol (CAS 67-63-0)	PEL	980 mg/m3
		400 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm
		150 ppm
n-propyl acetate (CAS 109-60-4)	TWA	100 ppm
		400 ppm
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
		TWA

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
n-propyl acetate (CAS 109-60-4)	STEL	1050 mg/m3
		250 ppm
Propan-2-ol (CAS 67-63-0)	TWA	840 mg/m3
		200 ppm
Propan-2-ol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
	TWA	980 mg/m3 400 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical goggles are recommended.

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

**Skin protection**

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

**Physical state** Liquid.

**Form** Liquid.

**Color** Colorless.

**Odor** Not available.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -173.2 °F (-114 °C)

**Initial boiling point and boiling range** 176 °F (80 °C)

**Flash point** 57.2 °F (14.0 °C) Closed Cup

**Evaporation rate** Expected to be rapid.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 3.3 % v/v (100% ethyl alcohol)

**Flammability limit - upper (%)** 19 % v/v (100% ethyl alcohol)

**Vapor pressure** 44.6 mm Hg

**Vapor density** 1.6 (air = 1)

**Relative density** Not available.

<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Completely soluble.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	685.4 °F (363 °C) (100% ethyl alcohol)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Chlorine. Isocyanates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Prolonged skin contact may cause temporary irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
Ethyl alcohol (CAS 64-17-5)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	117 - 125 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	10470 mg/kg
Propan-2-ol (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12870 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	72.6 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	4710 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	

**Respiratory or skin sensitization****Respiratory sensitization** Not a respiratory sensitizer.**Skin sensitization** This product is not expected to cause skin sensitization.**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.**Carcinogenicity** Not classifiable as to carcinogenicity to humans.**IARC Monographs. Overall Evaluation of Carcinogenicity**

Propan-2-ol (CAS 67-63-0) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens**

Not listed.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not regulated.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.**Specific target organ toxicity - single exposure** Not classified.**Specific target organ toxicity - repeated exposure** Not classified.**Aspiration hazard** Not an aspiration hazard.**Chronic effects** Prolonged inhalation may be harmful.**12. Ecological information****Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethyl alcohol (CAS 64-17-5)			
<b>Aquatic</b>			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
	NOEC	Marine water algae	1580 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
	NOEC	Freshwater fish	250 mg/l
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
<b>Other</b>			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
<b>Terrestrial</b>			
Plant	EC50	Terrestrial plant	633 mg/kg dw
Propan-2-ol (CAS 67-63-0)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours
Fish	LC50	Pimephales promelas	9640 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	EC50	Daphnia magna	> 100 mg/l, 21 days
	NOEC	Daphnia magna	141 mg/l, 16 days
			30 mg/l, 21 days

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Propan-2-ol (CAS 67-63-0)	0.05
n-propyl acetate (CAS 109-60-4)	1.23

**Mobility in soil** The product is completely soluble in water.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1987
<b>UN proper shipping name</b>	Alcohols, n.o.s.
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	172, IB2, T7, TP1, TP8, TP28
<b>Packaging exceptions</b>	4b, 150
<b>Packaging non bulk</b>	202
<b>Packaging bulk</b>	242

**IATA**

<b>UN number</b>	UN1987
<b>UN proper shipping name</b>	Alcohols, n.o.s.
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

<b>UN number</b>	UN1987
<b>UN proper shipping name</b>	ALCOHOLS, N.O.S.
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-D

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

n-propyl acetate (CAS 109-60-4) Listed.  
Propan-2-ol (CAS 67-63-0) Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Propan-2-ol	67-63-0	5 - 18.05

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

#### Safe Drinking Water Act (SDWA)

Not regulated.

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl alcohol (CAS 64-17-5) Low priority  
n-propyl acetate (CAS 109-60-4) Low priority  
Propan-2-ol (CAS 67-63-0) Low priority

### US state regulations

#### US. Massachusetts RTK - Substance List

Ethyl alcohol (CAS 64-17-5)  
n-propyl acetate (CAS 109-60-4)  
Propan-2-ol (CAS 67-63-0)

#### US. New Jersey Worker and Community Right-to-Know Act

Ethyl alcohol (CAS 64-17-5)  
n-propyl acetate (CAS 109-60-4)  
Propan-2-ol (CAS 67-63-0)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl alcohol (CAS 64-17-5)  
n-propyl acetate (CAS 109-60-4)  
Propan-2-ol (CAS 67-63-0)

#### US. Rhode Island RTK

Ethyl alcohol (CAS 64-17-5)  
n-propyl acetate (CAS 109-60-4)  
Propan-2-ol (CAS 67-63-0)



## California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Propan-2-ol (CAS 67-63-0)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 09-September-2018

**Revision date** -

**Version #** 01

**HMIS® ratings** Health: 2  
Flammability: 3  
Physical hazard: 0

**Disclaimer** This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found at <http://www.greenfield.com/tc-po-us/>. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.