SAFETY DATA SHEET



1. Identification

Product identifier SDA 35A 200 Proof

Other means of identification None.

Recommended use General purpose solvent.

Recommended restrictionsUse in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc. **Address** 1101 Isaac Shelby Drive

Shelbyville, KY 40065

USA

 Telephone
 502.232.7600

 Fax
 502.633.6100

Company Name Greenfield Global USA Inc.

Address 58 Vale Road

Brookfield, CT 06804

USA

 Telephone
 203.740.3471

 Fax
 203.740.3481

Emergency phone number

USA CHEMTREC: 1.800.424.9300 (CCN 17213)
International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye

protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire:

Use appropriate media to extinguish.

Issue date: 11-September-2018

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

945391 Version #: 01 Revision date: -

classified (HNOC)

SDA 35A 200 Proof SDS US

1/8

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethyl alcohol	64-17-5	88.26 - 95.38
Ethyl acetate	141-78-6	4.50 - 4.62
Water	7732-18-5	0 - 7.24

Composition comments

All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

SDA 35A 200 Proof SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is completely soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Ethyl acetate (CAS 141-78-6)	PEL	1400 mg/m3	
		400 ppm	
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	;		
Components	Туре	Value	
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm	
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Ethyl acetate (CAS 141-78-6)	TWA	1400 mg/m3	
		400 ppm	
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protectionWear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

SDA 35A 200 Proof SDS US

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with

organic vapor cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Clear liquid; invisible vapor.

Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point > -123 - -114 deg C

Initial boiling point and boiling

range

Flash point

172.94 - 176 °F (78.3 - 80 °C)

Evaporation rate 3.3 (butyl acetate = 1)
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

3.3 % v/v (for 100% ethyl alcohol)

57.2 - 62.6 °F (14.0 - 17.0 °C) Closed Cup

(%)

Flammability limit - upper

(%)

19 % v/v (for 100% ethyl alcohol)

Vapor pressure 41.4 - 44.6 mm Hg (68 $^{\circ}$ F (20 $^{\circ}$ C))

Vapor density 1.6 (air = 1)

Relative density 6.649 - 6.82 lb/gal (60 °F (15.56 °C))

Solubility(ies)

Solubility (water) Completely soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 685.4 °F (363 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

SDA 35A 200 Proof SDS US

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Prolonged skin contact may cause temporary irritation. Skin contact

Causes serious eye irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components **Species Test Results**

Ethyl acetate (CAS 141-78-6)

Acute

Dermal

LD50 Rabbit > 18000 mg/kg

Inhalation

Vapor

LC50 Rat 58.6 mg/l, 4 hours per event

Oral

LD50 Rat 10170 mg/kg

Ethyl alcohol (CAS 64-17-5)

Acute

Inhalation

Vapor

LC50 Rat 117 - 125 mg/l, 4 Hours

Oral

LD50 Rat 10470 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

SDA 35A 200 Proof 5/8

945391 Issue date: 11-September-2018 Version #: 01 Revision date: -

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethyl alcohol (CAS 64-17-5)			
Aquatic			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
	NOEC	Marine water algae	1580 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
	NOEC	Freshwater fish	250 mg/l
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestial			
Plant	EC50	Terrestrial plant	633 mg/kg dw
sistence and degradability	No data is a	available on the degradability of this produc	t.
accumulative potential	No data ava	No data available for this product.	
oility in soil	The produc	The product is completely soluble in water.	
er adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

14. Transport information

ח	1	т

DT	
UN number	UN1170
UN proper shipping name	Ethyl alcohol solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.

disposal.

SDA 35A 200 Proof SDS US

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

24, IB2, T4, TP1 Special provisions

Packaging exceptions 4b, 150 Packaging non bulk 202 242 Packaging bulk

IATA

UN1170 **UN** number

UN proper shipping name Ethyl alcohol solution

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN1170 **UN** number

UN proper shipping name ETHYL ALCOHOL SOLUTION

Transport hazard class(es)

Class 3 Subsidiary risk **Packing group** Ш **Environmental hazards**

Marine pollutant No. F-E, S-D **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl acetate (CAS 141-78-6) Listed.

Not established.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

SDS US SDA 35A 200 Proof

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl acetate (CAS 141-78-6)

Ethyl alcohol (CAS 64-17-5)

Low priority

Low priority

US state regulations

US. Massachusetts RTK - Substance List

Ethyl acetate (CAS 141-78-6) Ethyl alcohol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

Ethyl acetate (CAS 141-78-6) Ethyl alcohol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl acetate (CAS 141-78-6) Ethyl alcohol (CAS 64-17-5)

US. Rhode Island RTK

Ethyl acetate (CAS 141-78-6) Ethyl alcohol (CAS 64-17-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(e) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Inventory name

Issue date 11-September-2018

Revision date Version # 01
HMIS® ratings Health: 2

United States & Puerto Rico

Flammability: 3 Physical hazard: 0

Disclaimer This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found

at http://www.greenfield.com/tc-po-us/. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the

time of writing.

SDA 35A 200 Proof SDS US

Yes

On inventory (ves/ne)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).