

SAFETY DATA SHEET

1. Identification

Product identifier Prop Solv No 2, 200 Proof
Other means of identification None.
Recommended use General purpose solvent.
Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc.
Address 1101 Isaac Shelby Drive
 Shelbyville, KY 40065
 USA
Telephone 502.232.7600
Fax 502.633.6100

Company Name Greenfield Global USA Inc.
Address 58 Vale Road
 Brookfield, CT 06804
 USA
Telephone 203.740.3471
Fax 203.740.3481

Emergency phone number
USA CHEMTREC: 1.800.424.9300 (CCN 17213)
International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2
Health hazards Serious eye damage/eye irritation Category 2
 Carcinogenicity Category 2
 Reproductive toxicity Category 2
 Specific target organ toxicity, single exposure Category 1 (central nervous system, optic nerve)
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (central nervous system, optic nerve).

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethyl alcohol	64-17-5	87.83 - 92.45
Methanol	67-56-1	3.71
2-Pentanone, 4-methyl-	108-10-1	1.92
n-Hexane	110-54-3	0.83
Toluene	108-88-3	0.1
Water	7732-18-5	0.00 - 4.62

Composition comments All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Narcosis. Headache. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 ml.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is completely soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	PEL	410 mg/m ³
		100 ppm
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³
		200 ppm
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m ³
		500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Pentanone, 4-methyl- (CAS 108-10-1)	STEL	300 mg/m3
		75 ppm
	TWA	205 mg/m3
		50 ppm
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m3
		250 ppm
	TWA	260 mg/m3
		200 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3
		50 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Pentanone, 4-methyl- (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
n-Hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedio ne, without hydrolysis	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
n-Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
n-Hexane (CAS 110-54-3)	Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Colorless.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -173.2 °F (-114 °C)

Initial boiling point and boiling range 176 °F (80 °C)

Flash point 57.2 - 62.6 °F (14.0 - 17.0 °C) Closed Cup

Evaporation rate Expected to be rapid.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 3.3 % v/v

Flammability limit - upper (%) 19 % v/v

Vapor pressure	44.6 mm Hg
Vapor density	1.6 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Completely soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	685.4 °F (363 °C) (100% Ethyl alcohol)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation. May be absorbed through the skin.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Narcosis. Headache. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 ml.

Information on toxicological effects

Acute toxicity May be harmful if swallowed.

Components	Species	Test Results
2-Pentanone, 4-methyl- (CAS 108-10-1)		
Acute		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Oral		
LD50	Rat	3200 mg/kg
Ethyl alcohol (CAS 64-17-5)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	117 - 125 mg/l, 4 Hours
Oral		
LD50	Rat	10470 mg/kg

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12200 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	28.1 mg/l, 4 Hours
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
2-Pentanone, 4-methyl- (CAS 108-10-1)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not regulated.		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	Causes damage to organs (central nervous system, optic nerve).	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
2-Pentanone, 4-methyl- (CAS 108-10-1)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 3682 mg/l, 24 hours
Fish	LC50	Pimephales promelas 505 mg/l, 96 Hours
<i>Chronic</i>		
Crustacea	EC50	Daphnia magna 78 mg/l, 21 days
Fish	NOEC	Pimephales promelas 57 mg/l, 31 days
Ethyl alcohol (CAS 64-17-5)		
Aquatic		
Algae	EC10	Freshwater algae 11.5 mg/l, 72 hours
	EC50	Freshwater algae 275 mg/l, 72 hours
		Marine water algae 1900 mg/l
	NOEC	Marine water algae 1580 mg/l
Fish	LC50	Freshwater fish 11200 mg/l, 24 hours
	NOEC	Freshwater fish 250 mg/l

Components		Species	Test Results
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestrial			
Plant	EC50	Terrestrial plant	633 mg/kg dw
Methanol (CAS 67-56-1)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	> 10000 mg/l, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	15400 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Pentanone, 4-methyl- (CAS 108-10-1)	1.31
Methanol (CAS 67-56-1)	-0.77
Toluene (CAS 108-88-3)	2.73
n-Hexane (CAS 110-54-3)	3.9

Mobility in soil The product is completely soluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1987
UN proper shipping name	Alcohols, n.o.s. (Ethyl alcohol; Methanol)

Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	172, IB2, T7, TP1, TP8, TP28
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1987
UN proper shipping name	Alcohols, n.o.s. (Ethyl alcohol; Methanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethyl alcohol; Methanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Pentanone, 4-methyl- (CAS 108-10-1)	Listed.
Methanol (CAS 67-56-1)	Listed.
n-Hexane (CAS 110-54-3)	Listed.
Toluene (CAS 108-88-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-Pentanone, 4-methyl-	108-10-1	1.92
Methanol	67-56-1	3.71

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Pentanone, 4-methyl- (CAS 108-10-1)
Methanol (CAS 67-56-1)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-Pentanone, 4-methyl- (CAS 108-10-1) 35 %WV
Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

2-Pentanone, 4-methyl- (CAS 108-10-1) 6715
Toluene (CAS 108-88-3) 594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

2-Pentanone, 4-methyl- (CAS 108-10-1) Low priority
Ethyl alcohol (CAS 64-17-5) Low priority

US state regulations

US. Massachusetts RTK - Substance List

2-Pentanone, 4-methyl- (CAS 108-10-1)
Ethyl alcohol (CAS 64-17-5)
Methanol (CAS 67-56-1)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

2-Pentanone, 4-methyl- (CAS 108-10-1)
Ethyl alcohol (CAS 64-17-5)
Methanol (CAS 67-56-1)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Pentanone, 4-methyl- (CAS 108-10-1)
Ethyl alcohol (CAS 64-17-5)
Methanol (CAS 67-56-1)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

2-Pentanone, 4-methyl- (CAS 108-10-1)
Ethyl alcohol (CAS 64-17-5)
Methanol (CAS 67-56-1)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

California Proposition 65



WARNING: This product can expose you to chemicals including 2-Pentanone, 4-methyl-, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: November 4, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

2-Pentanone, 4-methyl- (CAS 108-10-1) Listed: March 28, 2014

Methanol (CAS 67-56-1) Listed: March 16, 2012

Toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

n-Hexane (CAS 110-54-3) Listed: December 15, 2017

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Pentanone, 4-methyl- (CAS 108-10-1)

Methanol (CAS 67-56-1)

n-Hexane (CAS 110-54-3)

Toluene (CAS 108-88-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-December-2018

Revision date 07-February-2019

Version # 02

HMIS® ratings Health: 4*
Flammability: 3
Physical hazard: 0

Disclaimer This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found at <http://www.greenfield.com/tc-po-us/>. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.