



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 1 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 1– IDENTIFICATION OF SUBSTANCE AND OF SUPPLIER

PRODUCT NAME: CARBON FILTERED GRAIN NEUTRAL SPIRITS (19%) VOL.

SYNONYMS: Ethanol, Alcohol, Ethyl Alcohol 38 US proof, Ethyl Alcohol DPS, (19% vol.) Ethyl Alcohol DS (19% vol), Ethyl Alcohol VS (19% vol.), Neutral Grain Spirits (19% vol.)

CHEMICAL FAMILY: Alcohols

RECOMMENDED USE: General purpose organic solvent, aerosols, cosmetics, pharmaceuticals, etc.

RESTRICTIONS ON USE: Refer to the alcohol control authority in country in which the product is to be used– Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in US etc.

SUPPLIER: **Greenfield Global Inc.**
6985 Financial Drive, Mississauga, Ontario, Canada L5N 0G3
Web page: <http://www.greenfield.com/>

NON-EMERGENCY INFORMATION PHONE NUMBER: (905) 790-7500
EMERGENCY PHONE NUMBER: CANUTEC (613) 996-6666

SECTION 2– HAZARDS IDENTIFICATION

GHS label elements, including precautionary statements:



Signal Word:
DANGER!

Hazard statement(s)

H2226 Flammable liquid and vapor.
H315 + H320 Causes skin and eye irritation
H335 May cause respiratory irritation.

Precautionary statement(s)

P501 Dispose of contents and container to an approved waste disposal plant.
P240 Ground/bond container and receiving equipment.
P337 + P313 If eye irritation persists: Get medical attention.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN.



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 2 OF 9
EFFECTIVE DATE: May 14, 2020

(SECTION 2 HAZARDS IDENTIFICATION CONTINUED)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
P233 Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P243 Take precautionary measures against static discharge.
P241 Use explosion-proof electrical, ventilating, and lighting equipment.
P242 Use only non-sparking tools.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves and eye and face protection.

GHS Classification(s)

Flammable Liquids (Category 2)
Eye irritation (Category 2B)
Skin irritation (Category 2)
Specific target organ toxicity - single exposure (Category 3)

Other hazards which do not result in classification:

Potential health Effects:

Organ	Description
Eyes	Can cause eye irritation. Common symptoms include stinging, tearing, and redness.
Ingestion	Can cause gastrointestinal irritation with nausea, vomiting and diarrhea. Systemic toxicity and acidosis can occur. Advanced stages can lead to respiratory failure,, kidney failure, coma and death.
Inhalation	Causes respiratory tract irritation. Can cause narcotic effects in high concentration. Vapors may cause dizziness or suffocation. Systemic toxicity and acidosis can occur. Advanced stages can lead to respiratory failure,, kidney failure, coma and death.
Skin	Causes moderate skin irritation. Can cause dermatitis by de-fating the skin from prolonged or repeated contact



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 3 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 3– COMPOSITION AND INFORMATION ON INGREDIENTS

CHEMICAL NAME: ETHYL ALCOHOL (19% VOL)
COMMON NAME/ SYNONYM: Ethanol, Alcohol, Ethyl Alcohol 38 US proof, Ethyl Alcohol DPS, 19% vol, Ethyl Alcohol DS, 19% vol.

INGREDIENT	% VOLUME	CAS NO.	EINECS NO.
Ethyl Alcohol	19	64-17-5	200-578-6
Water	balance	7732-18-5	231-791-2

SECTION 4– FIRST AID MEASURES

<u>INHALATION</u>	<ul style="list-style-type: none"> Remove victim to fresh air. Artificial respiration should be given if breathing has stopped and cardiopulmonary resuscitation if heart has stopped. Oxygen may be given if necessary. Seek medical attention immediately.
<u>SKIN</u>	<ul style="list-style-type: none"> Flush contaminated area with water for at least 20 minutes. Remove contaminated clothing under running water. Completely decontaminate clothing before re-use, or discard. If irritation occurs seek medical attention.
<u>EYES</u>	<ul style="list-style-type: none"> Immediately flush eyes with water for at least 20 minutes, holding the eyelids open. Seek medical attention immediately.
<u>INGESTION</u>	<ul style="list-style-type: none"> Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim drink about 250ml (8fl. oz.) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Seek medical assistance.
<u>NOTES TO PHYSICIAN</u>	<ul style="list-style-type: none"> Symptoms of ethanol intoxication vary with the alcohol level of the blood. Mild alcohol intoxication occurs at blood levels between 0.05-0.15% and approximately 25% of individuals will show signs of intoxication at these levels. Above 0.15% the person is definitely under the influence of ethanol and 50-95% of individuals at this level are clinically intoxicated. Severe poisoning occurs when the blood ethanol level is 0.3-0.5%. Above 0.5% the individual will be comatose and death can occur. The unabsorbed ethanol should be removed by gastric lavage after intubating the patient to prevent aspiration. Avoid the use of depressant drugs or the excessive administration of fluids.

SECTION 5– FIRE FIGHTING MEASURES

<u>EXTINGUISHING MEDIA</u>	<ul style="list-style-type: none"> Apply alcohol-type or all-purpose-type foams by manufacturers' recommended techniques for large fires. Use carbon dioxide or dry chemical media for small fires. Water is generally unsuitable for large open pools of alcohol and may help to spread the fire.
<u>UNUSUAL FIRE AND EXPLOSION HAZARDS</u>	<ul style="list-style-type: none"> Vapours form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from handling point.
<u>SPECIAL FIREFIGHTING PROCEDURES</u>	<ul style="list-style-type: none"> Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapours; reignition is possible. Use self-contained breathing apparatus and protective clothing.



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 4 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 6– ACCIDENTAL RELEASE MEASURES

SPILL

- Contain spilled material.
- Provide adequate ventilation. Provide adequate personnel protective equipment for responders.
- Remove sources of heat, sparks or flames.
- Spill should be collected in suitable containers or absorbed on a suitable absorbent material for subsequent disposal. Such containers used to contain spilled material and absorbent should be sealed off, otherwise the collected alcohol will evaporate from them.

WASTE DISPOSAL

- Waste material should be disposed of in an approved incinerator or in a designated landfill site, in compliance with all federal, provincial and local government regulations.

SECTION 7– HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

- Keep away from heat, sparks and flames.
- Keep container closed when not in use.
- Use with adequate ventilation.
- Avoid breathing vapours.
- Avoid contact with eyes and skin.
- Wash exposed skin thoroughly after handling.
- Take precautions to prevent static electricity build-up when transferring contents.

OTHER PRECAUTIONS

- Good personal hygiene practices are suggested, such as abstaining from eating, drinking and smoking in the workplace.

SECTION 8– EXPOSURE CONTROLS/ PERSONNEL PROTECTION

RESPIRATORY PROTECTION

- Up to 1000 ppm, an approved organic vapour cartridge respirator can be used.
- For concentrations above 1000 ppm, an air-supplying respirator is recommended.
- The user should consult a respirator guide, such as the Canadian Standards Association's guide Z94.4-M1982.

VENTILATION

- The ventilation system should be non-sparking, grounded and separate from other exhaust ventilation systems.
- Local ventilation is recommended when handling.

PROTECTIVE GLOVES

- Neoprene, butyl or natural rubber.

EYE PROTECTION

- Chemical resistant monogoggles when handling

OTHER PROTECTIVE EQUIPMENT

- Eye bath, safety shower and other protective equipment as required.

PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
 MSDS NO: **1001-19**

 PAGE 5 OF 9
 EFFECTIVE DATE: May 14, 2020

SECTION 9– PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Colourless liquid	
ODOUR	Typical ethanol/ lower alcohol odour	
ODOUR THRESHOLD	Approximately 0.1 to 5100 ppm for ethyl alcohol as reported in appendix 1 of the Canadian Standards Association guide Z94.4-M1982.	
PH	Not Applicable	
MELTING./ FREEZING POINT	Approximately minus 5 deg. C	
BOILING POINT RANGE	88-100 deg. C (boiling point 78.3 deg. C for 100% Ethanol)	
FLASH POINT	39.5 (Tag closed cup, ASTM D-56)	
EVAPORATION RATE	1.7 (butyl acetate = 1) for 100% Ethanol	
LOWER FLAMMABILITY LIMIT	3.3% V/V for 100% Ethanol	
UPPER FLAMMABILITY LIMIT	19 % V/V for 100% Ethanol	
VAPOR PRESSURE	44 mm Hg @ 20 deg. C, for 100% Ethanol	
VAPOUR DENSITY	1.56 (air=1)	
RELATIVE DENSITY (LIQUID)	0.9725 @ 20°C	
SOLUBILITY IN WATER	Complete	
SOLUBILITY IN OIL- COEFFICIENT OF WATER/OIL DISTRIBUTION	Separates from oil	
PARTITION COEFFICIENT N– OCTANOL/ WATER	0.032 approx.	
AUTO- IGNITION TEMPERATURE	Approx. 370 deg. C for 100% Ethanol	
DECOMPOSITION TEMPERATURE	Specific data not available	
VISCOSITY	Approx. 1.35 cp @ 20 deg. C for 100% Ethanol	
% VOLATILES BY VOLUME	100	
CHEMICAL FORMULA	Ethanol: C ₂ -H ₅ -OH Water: H ₂ O	Molecular weight: 46.07 Molecular weight 18.02

SECTION 10– STABILITY AND REACTIVITY

CHEMICAL STABILITY/ REACTIVITY	Stable
CONDITIONS TO AVOID	Sources of ignition
POSSIBILITY OF HAZARDOUS REACTIONS/ INCOMPATIBILITIES	Oxidizing materials
HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS	Burning can produce carbon monoxide and/or carbon dioxide and/or formaldehyde.
HAZARDOUS POLYMERIZATION	Will not occur
CONDITIONS TO AVOID	None currently known



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 6 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 11– TOXICOLOGICAL INFORMATION

INGREDIENT	% V/V	TLV, ppm	LC50, ppm/4h.	LD50, mg/kg	LD50, mg/kg
			RAT, INHAL.	RAT, ORAL	RABBIT, SKIN
(1) Ethyl Alcohol	19	1000	31,623	7,060	20,000
(2) Water	Balance	NA	NA	NA	NA

REFERENCES: ACGIH (1988-1989), RTECS (1983).

INGESTION

- May cause dizziness, faintness, drowsiness, decreased awareness and responsiveness, euphoria, abdominal discomfort, nausea, vomiting, staggering gait, lack of coordination and coma.

SKIN ABSORPTION

- No adverse effects with normal skin. However, potentially harmful amounts of material may be absorbed across markedly abraded skin when contact is sustained, particularly in children.

INHALATION

- High vapour concentrations may cause a burning sensation in the throat and nose, stinging and watering in the eyes.
- At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting may occur.

SKIN CONTACT

- Mild irritant.
- Repeated or prolonged exposure may lead to dermatitis, erythema and scaling.

EYE CONTACT

- Severe eye irritant.
- Vapours can irritate eyes.
- Eye damage from contact with liquid is reversible and proper treatment will result in healing within a few days.
- Damage is usually mild to moderate conjunctivitis, seen mainly as redness of the conjunctiva.

EFFECT OF REPEATED OVEREXPOSURE

- Long term repeated oral exposure to ethanol may result in the development of progressive liver injury with fibrosis.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE

- Repeated exposure to ethanol may exacerbate liver injury produced from other causes.

OTHER– REPRODUCTIVE TOXICITY OF ETHANOL WHEN CONSUMED AS A BEVERAGE DURING PREGNANCY

- Ethanol has been identified in studies as a developmental toxicant when consumed as a beverage during pregnancy.



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 7 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 12– ECOLOGICAL INFORMATION

Ethyl Alcohol CAS 64-17-5

Ecotoxicity (aquatic and terrestrial, where available):

Acute Fish toxicity (ETHANOL)

LC50 / 96 HOUR *Oncorhynchus mykiss* (rainbow trout) > 10,000 mg/l

LC50 / 96 HOUR *Pimephales promelas* (fathead minnow) > 13,400 mg/l

Toxicity to aquatic plants (ETHANOL)

Growth inhibition / 96 HOURS *Chlorella vulgaris* (Fresh water algae) 1,000 mg/l

Toxicity to microorganisms (ETHANOL)

Toxicity Threshold / *Pseudomonas putida* 6,500 mg/l

Summary: Inhibition of cell multiplication begins.

Persistence and degradability:

Biodegradation is expected.

Bioaccumulative potential:

Biaccumulation is unlikely

Other adverse effects:

BOD: 740-840 mg/g





PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 8 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 13– DISPOSAL CONSIDERATIONS

SPILL

- Contain spilled material.
- Provide adequate ventilation and protective equipment.
- Remove sources of heat, sparks or flames.
- Spill should be collected in suitable containers or absorbed on a suitable absorbent material for subsequent disposal.

WASTE
DISPOSAL

- Waste material should be disposed of in an approved incinerator or in a designated landfill site, in compliance with all federal, provincial and local government regulations.

SECTION 14– TRANSPORT INFORMATION

This product is exempt from the following TDG requirements per clause 1.36—Class 3, Flammable Liquids, Alcoholic Beverage, and Aqueous Solution of Alcohol Exemption, when shipped exclusively within Canada: (also applies when shipped exclusively within US, per 27CFR 4.10 and 5.11)

- Part 3 (Documentation),
- Part 4 (Dangerous Goods Safety Marks)
- Part 5 (Means of Containment),
- Part 6 (Training),
- Part 7 (Emergency Response Assistance Plan),
- Part 8 (Reporting)
- Part 9 (Road)
- Part 10 (Rail).

IMDG

UN-Number: UN1170 Class: 3 Packing Group: III

EMS-No: F-E, S-D

Proper shipping name: ETHANOL SOLUTIONS

Marine pollutant: No

IATA

SECTION 15– REGULATORY INFORMATION

All ingredients are on the following inventories or are exempted from listing:

Country Notification

Australia	AICS
Canada	DSL
China	IECS
European Union	EINECS
Japan	ENCS/ISHL
Korea	ECL
New Zealand	NZIoC
Philippines	PICCS
USA	TSCA

California Prop 65 Components

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm when drunk as a beverage: (ETHYL ALCOHOL) CAS No. 64-17-5 Revision Date: December 11, 2009



PRODUCT NAME: **Carbon Filtered Grain Neutral Spirits (19% vol.)**
MSDS NO: **1001-19**

PAGE 9 OF 9
EFFECTIVE DATE: May 14, 2020

SECTION 16– OTHER INFORMATION

PREPARED BY: Alcohol QA, Technical Services, and Regulatory Affairs Department

PHONE NUMBER: (905) 790-7500



GREENFIELD GLOBAL URGES EACH CUSTOMER OR RECIPIENT OF THIS MSDS TO STUDY IT CAREFULLY TO BECOME AWARE OF AND UNDERSTAND THE HAZARDS ASSOCIATED WITH THE PRODUCT. THE READER SHOULD CONSIDER CONSULTING REFERENCE WORKS OR INDIVIDUALS WHO ARE EXPERTS IN VENTILATION, TOXICOLOGY OR FIRE PREVENTION, AS NECESSARY OR APPROPRIATE TO USE AND UNDERSTAND THE DATA CONTAINED IN THIS MSDS.

TO PROMOTE SAFE USE AND HANDLING OF THIS PRODUCT, EACH CUSTOMER OR RECIPIENT SHOULD

- (1) NOTIFY EMPLOYEES, AGENTS, CONTRACTORS AND OTHERS WHO MAY USE THIS MATERIAL, OF THE INFORMATION IN THIS MSDS AND ANY OTHER INFORMATION REGARDING HAZARDS OR SAFETY,
- (2) FURNISH THIS SAME INFORMATION TO EACH CUSTOMER FOR THE PRODUCT, AND
- (3) REQUEST CUSTOMERS TO NOTIFY THEIR EMPLOYEES, CUSTOMERS, AND OTHER USERS OF THE PRODUCT OF THIS INFORMATION.